
专业制造工艺 享受卓越品质
Enjoy Excellent Quality Manufacturing Process

上嘉®






SHANGJIA
Gate Valves Series
上嘉闸阀系列

上海上嘉阀门制造有限公司
Shanghai Shangjia Valve Manufacturing Co.,ltd.









企业简介/让您了解现在的上嘉

上海上嘉阀门制造有限公司(原名上海市嘉定阀门厂)，创建于1956年，有五十多年生产高中压阀门历史。雄厚的技术力量，高素质的管理团队，良好的加工与检测设备，完善的质量保证体系，是一家现代化专业研发、制造和销售多种优质阀门的企业。

公司始终坚持以“科技求发展，质量创品牌”的企业理念，专心致力于各类阀门的研发和生产。近年来公司和有关科学研究院、合肥通用所、设计院、国内知名阀门专家携手合作。共同开发以国代进，具有超强防腐、耐磨性能好阀门。主要生产闸阀、截止阀、止回阀、球阀、蝶阀、陶瓷密封耐磨阀、大流量直通阀、水利控制阀。可按照最新的ANSI、API、DIN、BS、JIS、GB、SH、HG标准设计制造。所生产的阀门主体材料有WCB、A105、LCB、WC1、WC6、WC9、CF8、CF8M、CF3、CF3M、C5、F11、F321、F304、F316、F347及其它特殊材质。工作压力从1.0MPa～42.0MPa及150Lb～2500Lb，工作温度-196～950℃。产品广泛应于于石油、化工、电站、化纤、煤化工、化肥、供排水、城建等多种行业。质量稳定可靠，深受用户好评。

“上嘉”阀门，我们将充分发挥企业优势，人才建设为先导，技术创新为基础，不断提高管理水平，应用新技术、新工艺、新材料，积极研发新产品。进一步开拓国际、国内市场，给用户提供优质产品和一流的服务。力争成为中国阀门行业的龙头企业。

公司竭诚欢迎各界朋友莅临指导洽谈业务，愿与您携手并进，共创美好明天。

目录 CONTENTS

闸阀系列Gate Valve……1–8

气动闸阀 Pneumatic Gate Valve ……9–11

水封闸阀 Water–Sealetl Gate Valve……12–17

排渣闸阀 Dregs-eduction Gate Valve……18

带吹扫孔闸阀 With Ablution Holes Forming Gate Valve……19-20

低温闸阀 Cryogenic Gate Valve……21-23

保温闸阀 Jacket Gate Valve……24

平板闸阀 Flat Gate Valve……25

单闸板平板闸阀 Thro-conduit Gate Valve……26-41

双闸板平板闸阀 Double-Flat Gate Valve……42-44

油田专用平板闸阀 Special Flat Gate Valve for Oilfield……45-46

美标阀门系列 ANSI Valve……47

磅级闸阀 ANSI Gate Valve……48-49

磅级低温闸阀 ANSI Cryogenic Gate Valve……50-52

锻钢阀门系列 Forged Valve……53

锻钢闸阀 Forged Gate Valve……54

弹性座封闸阀 Flexible Seal Gate Valve……55-56

主要特点

全通径，明杆带支架

中法兰螺栓连接

带导向的弹性闸板

美标结构改进型

阀杆升降，手轮不升降

伞齿轮操作选配

标准法兰连接



CHIEF FEATURES

FULL PORT, OUTSIDE SCREW AND YOKE(OS&Y)

BOLTED BONNET

FLEXINLE WEDGE,FULLY GUIDED

STRUCTURE IMPROVE ON API

RISING STEM AND NON-RISING HANDWHEEL

AVAILABLE WITH GEAR OPERATOR

FLANGED ENDS

产品规范 Product Specification


产品规范 Product Specification	设计规范 Design Spec.	结构长度 Face to Face	连接法兰 Flange End	试验与检验 Test & inspection	压力-温度 Pressure-Temp.	产品标识 Marking	供货规范 Supply
	GB/T 12234	GB/T 12221	JB/T 79	JB/T 9092	GB/T 9131	GB/T 12220	JB/T 7928

主要零部件材料 Main Part Material

零件名称	阀体材料Body Material Code				Part Name
阀体/阀盖	WCB	ZGCr5Mo	ZG1Cr18Ni9Ti/CF8	ZG1Cr18Ni12Mo2Ti/CF8M	Body/Bonnet
闸板	WCB	ZGCr5Mo	ZG1Cr18Ni9Ti/CF8	ZG1Cr18Ni12Mo2Ti/CF8M	Wedge
阀杆	Cr13	25Cr2MoV	1Cr18Ni9Ti	1Cr18Ni12Mo2Ti	Stem
填料	柔性石墨/Flexible Graphite		聚四氟乙稀/PTFE		Packing
垫片	18-8柔性石墨/18-8Flexible Graphite				Gasket
螺栓	35/35CrMo	25Cr2MoV	1Cr18Ni9	1Cr18Ni9	Bolt
适用温度	-29～425℃	-29～450℃	-40～200℃	-40～200℃	Applicable Temp.
适用介质	水、油品、蒸汽 Water,Oil,Steam	蒸汽、油品 Steam,Oil	硝酸类 Nitrc Acid	醋酸类 Acetic Acid	Applicable Medium

总机：021-59546368







主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN1.6MPa									WT (kg)
		L	D	D_1	D_2	b	Z–φd	H	H_1	D_0	
Z41H–16C Z40H–16C Z41W–16P Z40W–16P Z41Y–16P Z40Y–16P Z41W–16R Z40W–16R Z41Y–16I Z40Y–16I KZ41Y–16C KZ40Y–16C Z540H–16C Z540Y–16P	40	200	145	110	85	16	4–φ18	300	352	200	26.5
	50	250	160	125	100	16	4–φ18	658	438	240	29
	65	265	180	145	120	18	4–φ18	375	450	240	33
	80	280	195	160	135	20	8–φ18	433	528	280	45
	100	300	215	180	155	20	8–φ18	502	620	320	63
	125	325	245	210	185	22	8–φ18	612	753	360	108
	150	350	280	240	210	24	8–φ23	676	847	360	134
	200	400	335	295	265	26	12–φ23	820	1039	400	192
	250	450	405	355	320	30	12–φ25	969	1245	450	273
	300	500	460	410	375	30	12–φ25	1142	1472	560	379
	350	550	520	470	435	34	16–φ25	1280	1450	640	590
	400	600	580	525	485	36	16–φ30	1452	1887	640	850
	450	650	640	585	545	40	20–φ30	1541	2011	720	907
	500	700	705	650	608	44	20–φ34	1676	2181	720	958
	600	800	840	770	718	48	20–φ41	1874	2346	800	1112
	700	900	910	840	788	50	24–φ41	2083	2517	800	1290
	800	1000	1020	950	598	52	24–φ41	2400	2890	950	1485
	900	1100	1120	1050	998	54	28–φ41	2950	3316	1000	1773
	1000	1200	1255	1170	1110	56	28–φ48	3245	3600	1000	2160

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN2.5MPa									WT (kg)
		L	D	D_1	D_2	b	Z–φd	H	H_1	D_0	
Z41H–25 Z40H–25 Z41W–25P Z40W–25P Z41Y–25P Z40Y–25P Z41Y–25R Z40Y–25R Z41Y–25I Z40Y–25I KZ41Y–25 KZ40Y–25 Z540H–25 Z540Y–25P	40	200	145	110	85	18	4–φ18	300	352	200	18
	50	250	160	125	100	20	4–φ18	358	438	240	28
	65	265	180	145	120	22	8–φ18	375	450	240	33
	80	280	195	160	135	22	8–φ18	433	528	280	46
	100	300	230	190	160	24	8–φ23	502	620	320	64
	125	325	270	220	188	28	8–φ25	612	753	360	116
	150	350	300	250	218	30	8–φ25	676	847	360	141
	200	400	360	310	278	34	12–φ25	820	1039	400	213
	250	450	425	370	332	36	12–φ30	969	1245	450	290
	300	500	485	430	390	40	16–φ30	1142	1472	560	400
	350	550	550	490	448	44	16–φ34	1280	1450	640	631
	400	600	610	550	505	48	16–φ34	1452	1887	640	900
	450	650	660	600	555	50	20–φ34	1541	2011	720	1013
	500	700	730	660	610	52	20–φ41	1676	2181	720	1166
	600	800	840	770	718	56	20–φ41	1874	2346	800	1258
	700	900	955	875	815	60	24–φ48	2083	2517	800	1383
	800	1000	1070	990	930	64	24–φ48	2400	2890	950	1596
	900	1100	1180	1090	1025	66	28–φ54	2950	3316	1000	1865
	1000	1200	1305	1210	1140	68	28–φ58	3245	3600	1000	2351


主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0MPa										WT (kg)
		L	D	D_1	D_2	D_6	b	Z–φd	H	H_1	D_0	
Z41H–40 Z40H–40 Z40Y–40P Z40Y–40P Z41Y–40R Z40Y–40R Z41Y–40I Z40Y–40I KZ41Y–40 KZ40Y–40 Z540H–40 Z540Y–40P	40	200	145	110	85	76	18	4–φ18	323	369	200	29
	50	250	160	125	100	88	20	4–φ18	372	440	280	16.5
	65	280	180	145	120	110	22	8–φ18	305	473	280	39
	80	310	195	160	135	121	22	8–φ18	457	552	320	52
	100	350	230	190	160	150	24	8–φ23	552	671	360	80
	125	400	270	220	188	176	28	8–φ25	634	726	400	127
	150	450	300	250	218	204	30	8–φ25	708	883	400	154
	200	550	375	320	282	260	38	12–φ30	858	1086	450	263
	250	650	445	385	345	313	42	16–φ34	1015	1298	460	368
	300	750	510	450	408	364	46	16–φ34	1203	1535	640	547
	350	850	570	510	465	422	52	16–φ34	1341	1673	640	679
	400	950	665	585	535	474	58	20–φ41	1492	1903	720	953
	450	1050	680	610	560	524	60	20–φ41	1583	2215	800	1253
	500	1150	755	670	612	576	62	20–φ41	1792	2580	950	1589
	600	1350	890	795	730	678	62	20–φ41	2035	2916	950	1903

总机：021–59546368







主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN6.4MPa										WT (kg)
		L	D	D_1	D_2	D_6	b	Z–φd	H	H_1	D_0	
Z41H–64 Z40H–64 Z41Y–64P Z40Y–64P Z41Y–64R Z40Y–64R Z41Y–64I Z40Y–64I KZ41Y–64 KZ40Y–64 Z540H–64 Z540Y–64P	40	240	165	125	125	76	25	4–φ23	360	389	389	29
	50	250	175	135	105	88	26	4–φ23	372	448	448	34
	65	280	200	180	130	110	28	8–φ23	395	475	280	43
	80	310	210	170	140	121	30	8–φ23	458	553	320	60
	100	350	250	200	168	150	32	8–φ25	553	649	360	89
	125	400	295	240	202	176	36	8–φ30	638	779	400	140
	150	450	340	280	240	204	38	8–φ34	718	893	450	207
	200	550	405	345	300	260	44	12–φ34	873	1100	560	325
	250	650	470	400	352	313	48	12–φ41	1053	1332	840	467
	300	750	530	460	412	364	54	16–φ41	1203	1535	640	590
	350	850	595	525	475	422	60	16–φ41	1394	1863	720	681
	400	950	670	585	525	474	66	16–φ48	1645	2070	800	972
	450	1050	670	630	570	524	70	20–φ48	1903	2381	800	1269
	500	1150	800	705	640	576	70	20–φ54	2285	2600	950	1606
	600	1350	950	820	750	678	76	20–φ58	2601	3010	950	2123

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN10.0MPa										WT (kg)
		L	D	D_1	D_2	D_6	b	Z–φd	H	H_1	D_0	
Z41H–100 Z40H–100 Z41Y–100P Z40Y–100P Z41Y–100R Z40Y–100R Z41Y–100I Z40Y–100I KZ41Y–100 KZ40Y–100 Z540H–100 Z540Y–100P	40	240	165	125	95	76	26	4–φ23	360	389	280	51
	50	250	195	145	112	88	28	4–φ23	490	558	360	60
	65	280	220	170	138	110	32	8–φ25	540	622	400	70
	80	310	230	180	148	121	34	8–φ25	573	671	400	89
	100	350	265	210	172	150	38	8–φ30	575	671	400	130
	125	400	310	250	210	176	42	8–φ34	744	892	560	223
	150	450	350	290	250	204	46	12–φ34	800	972	560	295
	200	550	430	360	312	260	54	12–φ41	800	972	560	559
	250	650	500	430	382	313	60	12–φ41	1050	1305	640	640
	300	750	585	500	442	364	70	16–φ48	1208	1506	640	730
	350	850	655	560	498	422	76	16–φ54	1410	1915	720	850
	400	950	715	620	558	474	80	16–φ54	1655	2304	720	975


主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN16.0MPa										WT (kg)
		L	D	D_1	D_2	D_6	b	Z–φd	H	H_1	D_0	
Z41H–160 Z40H–160 Z41Y–160P Z40Y–160P Z41Y–160R Z40Y–160R Z41Y–160I Z40Y–160I KZ41Y–160 KZ40Y–160 Z540H–160 Z540Y–160P	40	240	175	125	92	76	32	4–φ27	350	395	320	32
	50	300	215	165	132	88	36	8–φ25	512	612	360	73
	65	340	245	190	152	110	44	8–φ30	560	677	360	110
	80	390	260	205	168	121	46	8–φ30	585	686	400	141
	100	450	300	240	200	150	48	8–φ34	631	751	450	185
	125	525	355	285	238	176	60	8–φ41	723	868	560	320
	150	600	390	318	270	204	66	12–φ41	820	997	640	462
	200	750	480	400	345	250	78	12–φ48	990	1224	720	711
	250	850	580	485	425	313	88	12–φ54	1104	1503	800	923
	300	950	665	570	510	364	100	16–φ54	1314	1934	800	1204
	350	–	640	559	424	414.5	86	20–φ42	1600	2315	950	1450
	400	–	705	616	487	471.5	89	20–φ45	1823	2660	950	1700

总机：021–59546368











主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN1.6MPa							选配电装 E.A.	WT (kg)
		L	D	D_1	D_2	b	Z–φd	H		
Z941H–16C Z940H–16C Z941W–16P Z941W–16P Z941Y–16P Z940Y–16P Z941Y–16R Z940Y–16R Z941Y–16I Z940Y–16I KZ941Y–16C KZ940Y–16C Z9B40H–16C Z9B40Y–16P	40	200	145	110	85	16	4–φ18	595	DZW15	56
	50	250	160	125	100	16	4–φ18	653	DZW20	59
	65	265	180	145	120	18	4–φ18	665	DZW20	62
	80	280	195	160	135	20	8–φ18	725	DZW20	74
	100	300	215	180	155	20	8–φ18	787	DZW20	92
	150	350	280	240	210	24	8–φ23	955	DZW30	161
	200	400	335	295	265	26	12–φ23	1105	DZW30	219
	250	450	405	355	320	30	12–φ25	1343	DZW45	376
	300	500	460	410	375	30	12–φ25	1516	DZW60	484
	350	550	520	470	435	34	16–φ25	1678	DZW60	695
	400	600	580	525	485	36	16–φ30	1849	DZW90	977
	450	650	640	585	545	40	20–φ30	1937	DZW90	1033
	500	700	705	650	608	44	20–φ34	2234	DZW120	1087
	600	800	840	770	718	48	20–φ41	2232	DZW180	1357
	700	900	910	840	788	50	24–φ41	2489	DZW250	1481
	800	1000	1020	950	898	52	24–φ41	2643	DZW350	1845
	900	1100	1120	1050	998	54	28–φ41	2935	DZW500	2100
	1000	1200	1255	1170	1110	56	28–φ48	3410	DZW500	2650

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN2.5MPa							选配电装 E.A.	WT (kg)
		L	D	D_1	D_2	b	Z–φd	H		
Z941H–25 Z940H–25 Z941W–25P Z940W–25P Z941Y–25P Z940Y–25P Z941Y–25R Z940Y–25R Z941Y–25I Z940Y–25I KZ941Y–25C KZ940Y–25C Z9B41H–25 Z9B41Y–25P	40	200	145	110	85	18	4–φ18	595	DZW15	60
	50	250	160	125	100	20	4–φ18	653	DZW20	64
	65	265	180	145	120	22	8–φ18	665	DZW20	65
	80	280	195	160	135	22	8–φ18	725	DZW20	79
	100	300	230	190	160	24	8–φ23	787	DZW20	98
	125	325	270	220	188	28	8–φ25	902	DZW30	154
	150	350	300	250	218	30	8–φ25	955	DZW30	168
	200	400	360	310	278	34	12–φ25	1105	DZW45	219
	250	425	425	370	332	36	12–φ30	1343	DZW45	390
	300	450	485	430	390	40	12–φ30	1416	DZW60	505
	350	550	550	490	448	44	16–φ30	1678	DZW60	736
	400	600	610	550	505	48	16–φ34	1849	DZW90	1027
	450	650	660	600	555	50	16–φ34	1937	DZW90	1139
	500	700	730	660	610	52	20–φ34	2234	DZW120	1228
	600	800	840	770	718	56	20–φ41	2432	DZW180	1502
	700	900	955	875	815	60	20–φ41	2489	DZW250	1617
	800	1000	1070	990	930	64	24–φ48	2643	DZW350	1923
	900	1100	1180	1090	1025	66	24–φ48	2935	DZW500	2200
	1000	1200	1305	1210	1140	68	28–φ54	2410	DZW500	2800

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0MPa								选配电装 E.A.	WT (kg)
		L	D	D_1	D_2	D_6	b	Z–φd	H		
Z941H–40 Z940H–40 Z941W–40P Z940W–40P Z941Y–40R Z940Y–40R Z941Y–40I Z940Y–40I KZ941Y–40 KZ940Y–40 Z9B41H–40 Z9B41Y–40P	40	200	145	110	85	76	18	4–φ18	617	DZW15	46
	50	250	160	125	100	88	20	4–φ18	665	DZW20	58
	65	280	180	145	120	110	22	8–φ18	680	DZW20	68
	80	310	195	160	135	121	22	8–φ18	752	DZW20	80
	100	350	230	190	160	150	24	8–φ23	846	DZW30	108
	150	450	300	250	218	204	30	8–φ25	1087	DZW45	258
	200	550	375	320	282	260	38	12–φ30	1243	DZW45	366
	250	650	445	385	345	313	42	12–φ34	1429	DZW60	472
	300	750	510	450	408	364	46	16–φ34	1608	DZW90	673
	350	850	570	510	465	422	52	16–φ34	1738	DZW90	804
	400	950	655	585	535	474	58	16–φ41	1897	DZW120	1081

总机：021–59546368

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN6.4MPa								选配电装 E.A.	WT (kg)
		L	D	D_1	D_2	D_6	b	Z–φd	H		
Z941H–64 Z940H–64	40	240	165	125	95	76	24	4–φ23	580	DZW20	52
	50	250	175	135	105	88	26	4–φ23	667	DZW20	68
Z941Y–64P Z940Y–64P	65	280	200	160	130	110	28	8–φ23	685	DZW20	72
	80	310	210	170	140	121	30	8–φ23	748	DZW30	88
Z941Y–64R Z940Y–64R	100	350	250	200	168	150	32	8–φ25	845	DZW30	117
	150	450	340	280	240	204	44	8–φ34	1009	DZW45	314
Z941Y–64I Z940Y–64I	200	550	405	345	300	260	44	12–φ34	1253	DZW60	432
	250	650	470	400	345	313	48	12–φ41	1449	DZW60	595
KZ941Y–25I KZ940Y–25I	300	750	530	460	412	361	54	16–φ41	1867	DZW90	721
Z9B41H–64 Z9B41Y–64P	350	850	595	525	475	422	60	16–φ41	1931	DZW120	863
	400	950	670	585	525	474	66	16–φ48	2017	DZW180	1129

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	PN10.0MPa								选配电装 E.A.	WT (kg)
		L	D	D_1	D_2	D_6	b	Z–φd	H		
Z941H–100 Z940H–100	40	241	165	125	95	76	26	4–φ23	730	DZW20	60
	50	250	195	145	112	88	28	4–φ25	781	DZW20	78
Z941Y–100P Z940Y–100P	65	280	220	170	138	110	32	8–φ25	830	DZW20	96
	80	310	230	180	148	121	34	8–φ25	865	DZW30	126
Z941Y–100R Z940Y–100R	100	350	265	210	172	150	38	8–φ30	1179	DZW30	134
	150	450	350	290	250	204	46	12–φ34	1201	DZW60	352
Z941Y–100I Z940Y–100I	200	550	430	360	312	260	54	12–φ41	1611	DZW90	484
	250	650	500	430	383	313	60	12–φ41	1903	DZW90	608
KZ941Y–100 KZ940Y–100	300	750	585	500	442	364	70	16–φ48	2054	DZW120	757
Z9B41H–100 Z9B41Y–100P	350	850	655	560	498	422	76	16–φ54	2132	DZW180	994
	400	950	715	620	558	474	80	16–φ54	2321	DZW250	1269

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN16.0MPa								选配电装 E.A.	WT (kg)
		L	D	D_1	D_2	D_6	b	Z–φd	H		
Z941H–160 Z940H–160	40	260	175	125	92	76	32	4–φ27	812	DZW20	93
	50	300	215	165	132	88	36	8–φ25	905	DZW20	101
Z941Y–160P Z940Y–160P	65	340	245	190	152	110	44	8–φ30	968	DZW20	137
	80	390	260	205	168	121	46	8–φ30	978	DZW30	167
Z941Y–160R Z940Y–160R	100	450	300	240	200	150	48	8–φ34	1043	DZW30	211
	125	525	355	285	238	176	60	8–φ41	1248	DZW60	424
Z941Y–160I Z940Y–160I	150	600	390	318	270	204	66	12–φ41	1394	DZW90	588
	200	750	480	400	345	250	78	12–φ48	1621	DZW120	839
KZ941Y–160 KZ940Y–160	250	850	580	485	425	313	88	12–φ54	1953	DZW120	1050
	300	950	665	510	510	364	100	16–φ54	2411	DZW180	1265
Z9B41H–160 Z9B41Y–160P	350	–	640	559	424	414.5	83	20–φ42	2850	DZW250	1613
	400	–	705	616	481	471.5	89	20–φ45	3293	DZW250	2100





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN1.6MPa									WT (kg)
		L	D	D_1	D_2	b	Z–φd	H	H_1	D_0	
CZA6s40H–16C CZA6s40Y–16P CZA6s40Y–16R	50	250	160	125	100	16	4–φ18	950	570	180	36
	65	270	180	145	120	18	4–φ18	1050	596	180	53
	80	280	195	160	135	20	8–φ18	1080	635	200	72
	100	300	215	180	155	20	8–φ18	1145	645	250	90
	125	325	245	210	185	22	8–φ18	1240	685	250	120
	150	350	280	240	210	24	8–φ18	1300	720	320	132
	200	400	335	295	265	26	12–φ23	1660	940	400	258
	250	450	405	355	320	30	12–φ25	1790	1020	400	297
	300	500	460	410	375	30	12–φ25	1990	1150	450	420
	350	550	520	470	435	34	16–φ25	2090	1170	450	558
	400	600	580	525	485	36	16–φ30	2290	1325	500	540
	450	650	640	585	545	40	20–φ30	2485	1465	500	1110
	500	700	705	650	608	44	20–φ34	2640	1590	550	1380
	600	800	840	770	718	48	20–φ41	2940	1720	550	1620
	700	900	910	840	788	50	24–φ41	3450	1960	600	1966
	800	1000	1020	950	898	52	24–φ41	3650	2190	600	2282
	900	1100	1120	1050	998	54	28–φ41	3815	2400	800	2495
	1000	1200	1255	1170	1110	56	28–φ48	4000	2650	800	2760

总机：021–59546368

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN2.5MPa									WT (kg)
		L	D	D_1	D_2	b	Z–φd	H	H_1	D_0	
CZA6s40H–25 CZA6s40Y–25P CZA6s40Y–25R	50	250	160	125	100	20	4–φ18	950	570	180	38
	65	270	180	145	120	22	8–φ18	1050	596	180	55
	80	280	195	160	135	22	8–φ18	1080	635	200	76
	100	300	230	190	160	24	8–φ23	1145	645	250	94
	125	325	270	220	188	28	8–φ25	1210	685	250	126
	150	350	300	250	218	30	8–φ25	1300	720	320	136
	200	400	360	320	278	34	12–φ25	1660	940	400	265
	250	450	425	370	332	36	12–φ30	1790	1020	400	300
	300	500	485	430	390	50	16–φ30	1990	1150	450	436
	350	550	550	490	448	44	16–φ34	2090	1170	450	580
	400	600	610	550	505	48	16–φ34	2290	1325	500	860
	450	650	660	600	555	50	20–φ34	2485	1465	500	1260
	500	700	730	660	610	52	20–φ41	2640	1590	550	1420
	600	800	840	770	718	56	20–φ41	2940	1720	550	1710
	700	900	955	875	815	60	24–φ48	3450	1960	600	2105
	800	1000	1070	990	930	64	24–φ48	3650	2190	600	2310
	900	1100	1180	1090	1025	66	28–φ54	3815	2400	800	2620
	1000	1200	1305	1210	1140	68	28–φ54	4000	2650	800	2960

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0MPa										WT (kg)
		L	D	D_1	D_2	D_6	b	Z–φd	H	H_1	D_0	
CZA6s40H–40 CZA6s40Y–40P CZA6s40Y–40R	50	250	160	125	100	88	20	4–φ18	950	570	200	42
	65	280	180	145	120	110	22	8–φ18	1050	596	200	68
	80	320	195	160	135	121	22	8–φ18	1080	635	250	84
	100	350	230	190	160	150	24	8–φ23	1145	645	320	102
	125	400	270	220	188	176	28	8–φ25	1210	700	320	135
	150	450	300	250	218	204	30	8–φ25	1330	750	400	156
	200	550	375	320	282	260	38	12–φ30	1660	940	400	276
	250	650	445	385	345	313	42	12–φ34	1820	1050	450	306
	300	750	510	450	408	364	46	16–φ34	1990	1150	450	510
	350	850	570	510	465	422	52	16–φ34	2110	1190	500	720
	400	950	655	585	535	474	58	16–φ41	2335	1370	550	1050
	450	1050	680	610	560	524	60	20–φ41	2490	1510	550	1320
	500	1150	755	670	612	576	62	20–φ48	2640	1590	550	1800
	600	1350	890	795	730	678	62	20–φ54	2940	1720	600	2160

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN6.4MPa										WT (kg)
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	D_0	
CZA6s40H-64 CZA6s40Y-64P CZA6s40Y-64R	50	250	175	135	105	88	26	4-φ23	950	570	200	48
	65	280	200	160	130	110	28	8-φ23	1050	596	200	75
	80	310	210	170	140	121	30	8-φ23	1080	635	250	93
	100	350	250	200	168	150	32	8-φ23	1145	645	320	120
	125	400	295	240	202	176	36	8-φ30	1250	700	400	168
	150	450	340	280	240	204	38	8-φ34	1330	750	400	216
	200	550	405	345	300	260	44	12-φ34	1660	940	400	336
	250	650	470	400	352	313	48	12-φ41	1820	1050	450	396
	300	750	530	460	412	364	54	16-φ41	1990	1150	450	638
	350	850	595	525	475	422	60	16-φ41	2110	1190	500	810
	400	950	670	585	525	474	66	16-φ48	2335	1370	550	1140
	450	1050	670	630	570	524	70	20-φ48	2490	1500	550	1510
	500	1150	800	705	560	575	70	20-φ54	2640	1590	550	1920
	600	1350	930	820	750	678	76	20-φ58	2940	1720	600	2280

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN10.0MPa										WT (kg)
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	D_0	
CZA6s40H-100 CZA6s40Y-100P CZA6s40Y-100R	50	250	195	145	112	88	28	4-φ25	950	570	200	55
	65	280	220	170	138	110	32	8-φ25	1050	596	200	86
	80	310	230	180	148	121	34	8-φ25	1080	635	250	104
	100	350	265	210	172	150	38	8-φ30	1145	645	320	136
	125	400	310	250	210	176	42	8-φ34	1250	700	400	177
	150	450	350	290	250	204	46	12-φ34	1330	750	400	229
	200	550	430	360	312	260	54	12-φ41	1660	940	450	350
	250	650	500	430	382	313	60	12-φ41	1820	1050	450	430
	300	750	585	500	442	364	70	16-φ48	1990	1150	500	652
	350	850	655	560	498	422	76	16-φ54	2110	1190	550	890
	400	950	715	620	558	474	80	16-φ54	2335	1370	550	1210
	450	1050	770	675	615	524	84	16-φ58	2485	1500	600	1680
	500	1150	870	760	690	576	90	20-φ58	2640	1590	600	2100
	600	1350	990	875	800	678	95	24-φ58	2940	1720	800	2390

水封闸阀 Water-Sealetl Gate Valve

上嘉阀门

主要特点

全通径，明杆带支架

中法兰螺栓连接

弹性双闸板

填料室带0.6MPa水密封结构

系统与大气隔绝，气密性好

标准法兰连接

对焊连接





CHIEF FEATURES

FULL PORT，OUTSIDE SCREW AND YOKE（LS&Y）

BOLTED BONNET

FLEXIBLD DOUBLE WEDGE

RISING STEM AND NON-RISING HANDWHEEL

PACKING CHAMBER WITH 0.6MPa WATER SEAL STRUCTURE

SYSTEM ISOLATION FROM AIR，AIR SEAL WEL

FLANGED ENDS

BUTT-WELDING ENDS

产品规范Product specification

产品规范 Product Specification	设计规范 Design Spec.	结构长度 Face to Face	连接法兰 Flange End	试验与检验 Test &inspection	压力-温度 Pressure-Temp.	产品标识 Marking	供货规范 Supply
	GB/T 12234	GB/T 12221	JB/T 79	JB/T 9092	GB9131	GB/T 12220	JB/T 7928

主要零部件材料 Main Part Material

零件名称	零售部件材料 Part Material		Part Name
阀体/阀盖	WCB	1Cr5Mo	Body/Bonnet
闸　　板	WCB	1Cr5Mo	Wedge
阀　　杆	2Cr13	25Cr2MoV	Stem
密 封 副	HF+HF/STL+STL	STL+STL	Hard Trim
填　　料	柔性石墨/Flexible Graphete		Packing
垫　　片	18-8柔性石墨/18-8Flexible Graphite		Gasket
螺　　栓	35	35CrMo	Bolt
适用介质	-29～425℃	-29～540℃	Applicable Medium
适用温度	水、油品、蒸汽 Water,Oil,Steam	蒸汽、油品 Steam,Oil	Applicable Medium





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	PN1.6MPa								WT (kg)	选配电装E.A.		WT (kg)
		L	D	D_1	D_2	b	Z-φd	H	D_0		H	Type	
DS/Z44H-16C DS/Z944H-16C SZ40H-16C SZ940H-16C	50	250	160	125	100	16	4-φ18	330	300	23	620	DZW10	50
	65	270	180	145	120	18	4-φ18	435	300	34	714	DZW10	63
	80	280	195	160	135	20	8-φ18	491	350	38	765	DZW10	65
	100	300	215	180	155	20	8-φ18	573	350	52	840	DZW15	75
	125	325	245	210	185	22	8-φ18	582	400	86	852	DZW15	106
	150	350	280	240	210	24	8-φ23	605	400	104	875	DZW20	113
	200	400	335	295	265	26	12-φ23	739	450	159	1015	DZW20	189
	250	450	405	355	320	30	12-φ25	862	550	200	1125	DZW30	214
	300	500	460	410	375	30	12-φ25	990	650	258	1371	DZW45	353
	350	550	520	470	435	34	16-φ25	1139	750	501	1485	DZW60	602
	400	600	580	525	485	36	16-φ30	1523	850	605	1890	DZW60	698


主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN2.5MPa								WT (kg)	选配电装E.A.		WT (kg)
		L	D	D_1	D_2	b	Z-φd	H	D_0		H	Type	
DS/Z44H-25 DS/Z944H-25 SZ40H-25 SZ940H-25	50	250	160	125	100	20	4-φ18	330	300	25	620	DZW10	54
	65	270	180	145	120	22	8-φ18	435	300	36	714	DZW10	66
	80	280	195	160	135	22	8-φ18	491	350	42	765	DZW10	68
	100	300	230	190	160	24	8-φ23	573	350	55	840	DZW15	80
	125	325	270	220	188	28	8-φ25	582	400	89	852	DZW20	109
	150	350	300	250	218	30	8-φ25	605	400	110	875	DZW20	146
	200	400	360	310	278	34	12-φ25	739	450	162	1015	DZW30	191
	250	450	425	370	332	36	12-φ30	862	550	210	1125	DZW30	219
	300	500	485	430	390	40	16-φ30	990	650	266	1371	DZW45	257
	350	550	550	490	448	44	16-φ34	1139	750	515	1485	DZW60	607
	400	600	610	550	505	48	16-φ34	1523	850	620	1890	DZW60	705

总机：021-59546368





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0MPa								WT (kg)	选配电装E.A.		WT (kg)
		L	D	D_1	D_2	b	Z-φd	H	D_0		H	Type	
DS/Z44H-40 DS/Z944H-40 SZ44H-40 SZ944H-40	50	250	160	125	100	20	4-φ18	330	300	27	620	DZW10	55
	65	270	180	145	120	22	8-φ18	435	300	38	714	DZW10	65
	80	280	195	160	135	22	8-φ18	491	350	42	765	DZW15	70
	100	300	230	190	160	24	8-φ23	573	350	57	840	DZW20	86
	125	325	270	220	188	26	8-φ25	582	400	91	852	DZW20	120
	150	350	300	250	218	30	8-φ25	605	400	110	875	DZW30	138
	200	400	375	320	282	38	12-φ30	739	450	169	1015	DZW30	200
	250	450	445	385	345	42	12-φ34	862	550	207	1225	DZW40	290
	300	500	510	450	400	46	16-φ34	990	650	266	1371	DZW60	383
	350	550	570	510	465	52	16-φ34	1139	750	513	1507	DZW90I	601
	400	600	655	585	535	58	16-φ41	1523	850	627	1912	DZW120	866

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN6.4MPa									WT (kg)	选配电装E.A.		WT (kg)
		L	D	D_1	D_2	D_6	b	Z-φd	H	D_0		H	Type	
DS/Z44H-64 DS/Z944H-64 SZ40H-64 SZ940H-64	50	250	175	125	105	88	26	4-φ23	337	300	30	622	DZW10	58
	65	280	200	160	130	110	28	8-φ23	441	300	41	714	DZW15	69
	80	310	210	170	140	121	30	8-φ23	496	350	45	765	DZW20I	73
	100	350	250	200	168	150	32	8-φ25	578	400	62	840	DZW20I	90
	125	400	295	240	202	176	36	8-φ30	588	400	97	852	DZW30	124
	150	450	340	280	240	204	38	8-φ34	610	450	115	875	DZW30	142
	200	550	405	345	300	260	44	12-φ34	744	550	172	1195	DZW45	270
	250	650	470	400	352	313	48	12-φ41	867	650	211	1225	DZW60	317
	300	750	530	460	412	364	54	16-φ41	996	750	271	1393	DZW90	399
	350	850	595	525	475	422	60	16-φ41	1142	850	518	1507	DZW120I	467
	400	950	670	585	525	474	66	16-φ48	1537	900	633	2075	DZW180	882


主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN10.0MPa									WT (kg)	选配电装E.A.		WT (kg)
		L	D	D_1	D_2	D_6	b	Z-φd	H	D_0		H	Type	
DS/Z44H-100 DS/Z944H-100 SZ40H-100 SZ940H-100	50	250	195	145	112	88	28	4-φ25	337	300	34	622	DZW10	62
	65	280	220	170	138	110	32	8-φ25	441	300	46	714	DZW15	74
	80	310	230	180	148	121	34	8-φ25	496	350	50	765	DZW20I	78
	100	350	265	210	172	150	38	8-φ30	578	400	67	840	DZW30I	95
	125	400	310	250	210	176	42	8-φ34	588	400	102	852	DZW30	129
	150	450	350	290	250	204	46	12-φ34	610	450	121	875	DZW45	221
	200	550	430	360	312	260	54	12-φ41	744	550	178	1195	DZW60	235
	250	650	500	430	382	313	60	12-φ41	867	650	217	1225	DZW90I	345
	300	750	585	500	442	364	70	16-φ48	996	750	278	1393	DZW120I	409
	350	850	655	560	498	422	76	16-φ54	1142	850	524	1507	DZW180	773
	400	950	715	620	558	474	80	16-φ54	1537	950	640	2075	DZW250	892

总机：021-59546368





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	L	H	D_0	PN1.6MPa			PN2.5MPa		
					D	D_1	WT(kg)	D	D_1	WT(kg)
DS/Z64H-16C DS/Z64H-25 SZ60H-16C SZ60H-25	50	250	334	250	58	50	19	64	49	23
	65	270	439	250	75	65	32	82	67	35
	80	280	495	300	91	79	34	95	77	37
	100	300	575	350	110	97	44	117	101	49
	125	325	587	350	136	121	75	144	126	78
	150	350	607	350	163	146	82	172	158	105
	200	400	740	400	223	202	158	223	202	160
	250	450	863	400	278	254	184	278	254	188
	300	500	990	400	330	305	245	330	305	249
	350	550	1137	500	382	352	492	382	352	497
	400	600	1523	500	432	399	588	432	399	592
	450	650	1618	600	485	451	683	485	451	688
	500	700	1657	600	535	501	846	535	499	853
	600	800	1746	700	636	601	1013	636	599	1020

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	L	D	PN4.0MPa				PN6.4MPa				PN10.0MPa			
				D_1	H	D_0	WT (kg)	D_1	H	D_0	WT (kg)	D_1	H	D_0	WT (kg)
DS/Z64H-40 DS/Z64H-64 DS/Z64H-100 SZ60H-40 SZ60H-64 SZ60H-100	50	250	64	49	345	300	30	50	350	300	34	49	350	300	37
	65	270	83	67	441	300	38	66	447	300	41	64	447	300	44
	80	280	96	79	495	350	42	77	499	350	45	75	499	350	47
	100	300	117	101	575	350	52	99	582	400	55	97	582	400	57
	125	325	144	126	587	400	80	129	590	400	83	125	590	400	87
	150	350	172	152	607	400	107	150	611	450	110	145	611	450	113
	200	400	223	200	740	450	164	198	745	550	169	190	747	550	172
	250	450	278	252	863	550	191	246	867	650	195	236	869	650	198
	300	500	330	302	1008	650	254	294	1008	750	260	282	1013	750	265
	350	550	382	350	1142	750	499	342	1148	800	504	334	1148	850	508
	400	650	432	397	1527	850	598	387	1531	900	604	377	1533	950	610





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Product Type	公称通径 DN	L	H	PN1.6MPa		选配电装 E.A.	WT (kg)	PN2.5MPa		选配电装 E.A.	WT (kg)
				D	D_1			D	D_1		
DS/Z964H-16C DS/Z964H-25 SZ960H-16C SZ960H-25	50	250	620	58	50	DZW10	50	64	49	DZW10	54
	65	270	714	75	65	DZW10	63	82	67	DZW10	66
	80	280	765	91	79	DZW10	65	95	77	DZW10	68
	100	300	840	110	97	DZW15	75	117	101	DZW15	80
	125	325	852	136	121	DZW15	106	144	126	DZW20I	109
	150	350	875	163	146	DZW20I	113	172	158	DZW20I	146
	200	400	1015	223	202	DZW20	189	223	202	DZW30	191
	250	450	1125	278	254	DZW30	214	278	254	DZW30	219
	300	500	1371	330	305	DZW45	353	330	305	DZW45	257
	350	550	1485	382	352	DZW60	602	382	352	DZW60	607
	400	600	1890	432	399	DZW60	698	432	399	DZW90	705
	450	650	1989	485	451	DZW90	713	485	451	DZW120	720
	500	700	2041	535	501	DZW120	881	535	499	DZW120	888
	600	800	2285	636	601	DZW180	1250	636	599	DZW180	1275
	700	900	2347	726	691	DZW250	1938	726	689	DZW250	1946
	800	1000	2593	826	791	DZW350	2562	826	789	DZW350	2574


主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Product Type	公称通径 DN	L	D	PN4.0 Mpa		选配电装 E.A.	WT (kg)	PN6.4 Mpa		选配电装 E.A.	WT (kg)	PN10.0 Mpa		选配电装 E.A.	WT (kg)
				D_1	H			D_1	H			D_1	H		
DS/Z964H-40 DS/Z964H-64 DS/Z964H-100 SZ960H-40 SZ960H-64 SZ960H-100	50	280	64	49	620	DZW10	56	50	620	DZW10	57	49	622	DZW10	58
	65	310	83	67	714	DZW10	68	66	714	DZW15	71	64	718	DZW15	71
	80	350	96	79	767	DZW15	73	77	767	DZW20I	74	75	770	DZW20I	77
	100	400	117	101	845	DZW20I	82	99	845	DZW20I	85	97	845	DZW20I	89
	125	450	144	126	852	DZW20I	108	129	852	DZW30	111	125	852	DZW30	113
	150	550	172	152	875	DZW30	117	150	875	DZW30	117	145	965	DZW45	122
	200	650	223	200	1015	DZW30	193	198	1015	DZW45	193	190	1105	DZW60	195
	250	750	278	252	1215	DZW45	217	246	1215	DZW60	222	236	1237	DZW90I	235
	300	850	330	302	1371	DZW60	357	294	1371	DZW90I	362	282	1424	DZW120I	370
	350	950	382	350	1507	DZW90I	624	342	1507	DZW120I	631	334	1670	DZW180	641
	400	1050	432	397	1912	DZW120	701	387	1912	DZW180	713	377	2075	DZW250	725

总机：021-59546368





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	PN1.6/2.5MPa								WT (kg)
		L	D	D_1	D_2	b	Z-φd	H	D_0	
PZ41H-16C PZ941H-16C	50	250	160	125	100	16	4-φ18	335	250	60
	80	280	195	160	135	20	8-φ18	510	280	78
	100	300	215	180	155	20	8-φ18	685	300	96
	150	350	280	240	210	24	8-φ23	790	300	158
	200	400	335	295	265	26	12-φ25	885	350	222
	250	450	405	355	320	30	12-φ23	1015	400	289
	300	500	460	410	375	30	12-φ25	1190	450	365
	350	550	520	470	435	34	16-φ25	1350	500	558
	400	600	580	525	485	36	16-φ25	1460	500	850
	450	650	640	585	545	40	20-φ30	1620	550	1164
	500	700	705	650	608	44	20-φ34	1800	550	1482
PZ41H-25 PZ941H-25	50	250	160	125	100	20	4-φ18	335	250	99
	80	280	195	160	135	22	8-φ18	510	280	118
	100	300	230	190	160	24	8-φ23	685	300	147
	150	350	300	250	218	30	8-φ25	790	300	204
	200	400	360	310	278	34	12-φ25	885	350	273
	250	450	425	370	332	36	12-φ30	1015	400	373
	300	500	485	430	390	40	16-φ30	1190	450	478
	350	550	550	490	448	44	16-φ34	1350	500	680
	400	600	610	550	505	48	16-φ34	1460	500	1008
	450	650	660	600	555	50	20-φ34	1620	550	1344
	500	700	730	660	610	52	20-φ41	1800	550	1827


主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0/6.4MPa									WT (kg)
		L	D	D_1	D_2	D_6	b	Z-φd	H	D_0	
PZ41H-40 PZ941H-40	50	250	160	125	100	88	20	4-φ18	340	250	98
	80	310	195	160	135	121	22	8-φ18	508	300	126
	100	350	230	190	160	150	24	8-φ23	680	300	156
	150	450	300	250	218	204	30	8-φ25	800	400	228
	200	550	375	320	282	260	38	12-φ30	875	500	298
	250	650	445	385	345	313	42	12-φ34	1010	500	372
	300	750	510	450	408	364	46	16-φ34	1180	550	450
	350	850	570	510	465	422	52	16-φ34	1145	600	530
	400	950	655	585	535	474	58	16-φ41	1280	600	610
	450	1050	680	610	560	524	60	20-φ41	1415	700	690
	500	1150	755	670	612	576	62	20-φ48	1560	750	772
PZ41H-64 PZ941H-64	50	250	175	135	105	88	26	4-φ23	340	250	142
	80	310	210	170	140	121	30	8-φ23	508	300	168
	100	350	250	200	168	150	32	8-φ25	680	300	210
	150	450	340	280	240	204	38	8-φ34	800	400	270
	200	550	405	345	300	260	44	12-φ41	870	500	367
	250	650	470	400	352	313	48	12-φ41	1010	500	450
	300	750	530	460	415	364	54	16-φ41	1180	550	532
	350	850	595	525	475	422	60	16-φ41	1145	600	548
	400	950	670	585	525	474	66	16-φ48	1280	600	615
	450	1050	715	630	570	524	70	20-φ48	1415	700	695
	500	1150	800	705	610	576	76	20-φ54	1560	750	778







主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN2.5MPa								WT(kg)	
		L	D	D_1	D_2	D_6	Z-ϕd	H	D_0	F_1	F_2
Z_1仿41H–16C Z_2仿41H–16C Z_1仿41Y–16Ⅰ Z_2仿41Y–16Ⅰ Z_1仿41Y–16PⅠ Z_2仿41Y–16PⅠ Z_1仿41Y–16PⅡ Z_2仿41Y–16PⅡ	50	250	160	125	100	16	4-ϕ18	362	250	29	32
	65	270	180	145	120	18	4-ϕ18	395	250	33	36
	80	280	195	160	135	18	8-ϕ18	426	300	46	49
	100	300	215	180	155	20	8-ϕ18	470	300	63	66
	125	325	245	210	185	22	8-ϕ18	520	350	98	102
	150	350	280	240	210	24	8-ϕ23	590	350	125	128
	200	400	335	295	265	26	12-ϕ23	725	400	185	188
	250	450	405	355	320	30	12-ϕ25	865	450	260	263
	300	500	460	410	375	30	12-ϕ25	1000	550	365	368
	350	550	520	470	435	34	16-ϕ25	1140	600	498	505
	400	600	580	525	485	36	16-ϕ30	1285	650	685	688

总机：021–59546368

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN2.5MPa								WT(kg)	
		L	D	D_1	D_2	D_6	Z-φd	H	D_0	F_1	F_2
Z_1仿41H–25C Z_2仿41H–25C Z_1仿41Y–25Ⅰ Z_2仿41Y–25Ⅰ Z_1仿41Y–25PⅠ Z_2仿41Y–25PⅠ Z_1仿41Y–25PⅡ Z_2仿41Y–25PⅡ	50	250	160	125	100	20	4-φ18	362	250	31	34
	65	270	180	145	120	22	8-φ18	395	250	35	38
	80	280	195	160	135	22	8-φ18	426	300	47	50
	100	300	230	190	160	24	8-φ23	470	300	65	68
	125	325	270	220	188	28	8-φ25	520	350	100	103
	150	350	300	250	218	30	8-φ25	590	350	130	133
	200	400	360	310	278	34	12-φ25	725	400	195	198
	250	450	425	370	332	36	12-φ30	865	450	275	278
	300	500	485	430	390	40	16-φ30	1000	550	392	395
	350	550	550	490	448	44	16-φ34	1140	650	535	538
	400	600	610	550	505	48	16-φ34	1285	700	742	745

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0MPa									WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	D_0	F_1	F_2
Z_1仿41H–40C Z_2仿41H–40C Z_1仿41Y–40Ⅰ Z_2仿41Y–40Ⅰ Z_1仿41Y–40PⅠ Z_2仿41Y–40PⅠ Z_1仿41Y–40PⅡ Z_2仿41Y–40PⅡ	50	250	160	125	100	88	20	4-φ18	371	280	31	34
	65	280	180	145	120	110	22	8-φ18	391	280	40	44
	80	310	195	160	135	121	22	8-φ18	455	320	52	58
	100	380	230	190	160	150	24	8-φ23	551	360	81	88
	125	400	270	220	188	176	28	8-φ25	628	400	125	135
	150	450	300	250	218	204	30	8-φ25	708	400	145	159
	200	550	375	320	282	260	38	12-φ30	885	450	253	268
	250	650	445	385	345	313	42	12-φ34	1015	560	360	372
	300	750	510	450	408	364	46	16-φ34	1135	640	556	569
	350	850	570	510	465	422	52	16-φ34	1250	720	700	720
	400	950	655	585	535	474	58	16-φ41	1400	720	789	818

低温闸阀 Cryogenic Gate Valve

主要特点

全通径，全封闭，明杆带支架

中法兰螺栓连接

带导向的弹性闸板

美标结构改进型

加长保温颈

伞齿轮操作选配

标准法兰连接



CHIEF FEATURES

FULL PORT, OUTSIDE SCREW AND YOKE(OS&Y)

BOLTE D BONNET

FLEXIBLE WEDGE, FULLY GUIDED

STRUCTUIRE IMPROVE ON API

EXTENSION HOLDING NECK

AVAILABLE WITH GEAR OPERATOR

FLANGED ENDS

产品规范Product Specification


产品规范 Product Specification	设计规范 Design Spec.	结构长度 Face to Face	连接法兰 Flange End	试验与检验 Test &inspection	压力–温度 Pressure–Temp.	产品标识 Marking	供货规范 Supply
	JB/T 7749	JB/T 12221	JB/T 79	JB/T 9092	GB/T 9131	GB/T 12220	JB/T 7928

主要零部件材料Main Part Material

零件名称	零部件材料 Part material							Part Name
阀　体	LCB	LC1	LC2	LC3	LC4	CF8/CF8M	CF3/CF3M	Body
阀　盖	LCB	LC1	LC2	LC3	LC4	CF8/CF8M	CF3/CF3M	Bonnet
闸　板	LCB	LC1	LC2	LC3	LC4	CF8/CF8M	CF3/CF3M	Wedge
阀　杆	1Cr17Ni12			1Cr18Ni9Ti			0Cr14Ni12Mo2	Stem
密封副	STL+STL			STL+STL			STL+STL	Hard Trim
填　料	柔性石墨Flexible Graphite (聚四氟乙烯/PTFE)							Packing
垫　片	18–8柔性石墨Flexible Graphite							Gasket
螺　栓	1Cr17Ni12			1Cr18Ni9Ti			1Cr18Ni9Ti	Bolt
适用温度	-46℃	-60℃	-73℃	-10℃	-115℃	-196℃	-196℃	Applicable Temp.
适用介质	丙烷、丙烯、甲醇、乙烷、煤气、液氨 Propane,propyoene,Mathanol,Ethanol,Coal–Gas,Liquid Ammonia							Applicable Medium

总机：021–59546368





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN1.6MPa								WT (kg)
		L	D	D_1	D_2	b	Z–φd	H	D_0	
DZ40Y–16L	20	150	105	75	55	14	4–φ14	320	140	6
	25	160	115	85	65	14	4–φ14	350	160	7
	32	180	135	100	78	16	4–φ18	385	180	9
	40	200	145	110	85	16	4–φ18	420	200	15
	50	250	160	125	100	16	4–φ18	540	240	30
	65	265	180	145	120	18	4–φ18	610	240	34
	80	280	195	160	135	20	8–φ18	690	280	45
	100	300	215	180	155	20	8–φ18	780	300	64
	125	325	245	210	185	22	8–φ18	930	320	110
	150	350	280	240	210	24	8–φ23	980	360	135
	200	400	335	295	265	26	12–φ23	1180	400	195
	250	450	405	355	320	30	12–φ25	1390	450	275
	300	500	460	410	375	30	12–φ25	1620	560	380
	350	550	520	470	425	34	16–φ25	1810	640	594
	400	600	580	525	485	36	16–φ30	1970	640	725

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN2.5MPa								WT (kg)
		L	D	D_1	D_2	b	Z–φd	H	H	
DZ40Y–25L	20	150	105	75	55	16	4–φ14	320	140	6
	25	160	115	85	65	16	4–φ14	350	160	8
	32	180	135	100	78	18	4–φ18	385	180	10
	40	200	145	110	85	18	4–φ18	420	200	16
	50	250	160	125	100	20	4–φ18	540	240	30
	65	265	180	145	120	22	8–φ18	610	240	35
	80	280	195	160	135	22	8–φ18	690	280	47
	100	300	230	190	160	24	8–φ23	780	300	65
	125	325	270	220	188	28	8–φ25	930	320	110
	150	350	300	250	218	30	8–φ25	980	360	135
	200	400	360	310	278	34	12–φ25	1180	400	215
	250	450	425	370	332	36	12–φ30	1390	450	295
	300	500	485	430	390	40	16–φ30	1620	560	400
	350	550	550	490	448	44	16–φ34	1810	640	630
	400	600	610	550	505	48	16–φ34	1970	640	910

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0MPa									WT (kg)
		L	D	D_1	D_2	D_6	b	Z–ϕd	H	D_0	
DZ40Y–40L	20	150	105	75	55	51	16	4–ϕ14	330	140	7
	25	100	115	85	65	58	16	4–ϕ14	360	160	9
	32	180	135	100	78	66	18	4–ϕ18	440	180	11
	40	200	145	110	85	76	18	4–ϕ18	455	200	19
	50	250	160	125	100	88	20	4–ϕ18	575	280	28
	65	280	180	145	120	110	22	8–ϕ18	635	280	35
	80	310	195	160	135	121	22	8–ϕ18	715	320	50
	100	350	230	190	160	150	24	8–ϕ23	815	360	74
	125	400	270	220	188	176	28	8–ϕ25	965	400	115
	150	450	300	250	218	204	30	8–ϕ25	1025	400	135
	200	550	375	320	282	260	38	12–ϕ30	1225	450	215
	250	650	445	385	345	313	42	12–ϕ34	1440	560	184
	300	750	510	450	408	346	46	16–ϕ34	1665	640	405
	350	850	570	510	465	422	52	16–ϕ34	1880	640	600
	400	950	655	585	535	474	58	16–ϕ41	2050	720	750

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	PN6.4MPa									WT (kg)
		L	D	D_1	D_2	D_6	b	Z–ϕd	H	D_0	
DZ40Y–64L	20	190	125	90	68	51	20	4–ϕ18	330	100	8
	25	210	165	100	78	58	22	4–ϕ23	360	180	13
	32	230	150	110	82	66	24	4–ϕ23	410	180	24
	40	240	165	125	95	76	24	4–ϕ23	480	200	32
	50	250	175	135	105	88	26	4–ϕ23	585	200	39
	65	280	200	160	160	110	28	8–ϕ23	690	250	45
	80	310	210	170	140	121	30	8–ϕ23	745	300	60
	100	350	250	200	168	150	32	8–ϕ25	885	300	90
	125	400	295	240	202	176	36	8–ϕ30	958	350	140
	150	450	340	280	240	204	38	8–ϕ34	1050	350	205
	200	550	405	345	300	260	44	12–ϕ34	1240	400	330
	250	650	470	400	352	313	48	12–ϕ41	1460	500	468
	300	750	530	460	412	364	54	16–ϕ41	1690	640	600

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN10.0MPa									WT (kg)
		L	D	D_1	D_2	D_6	b	Z–ϕd	H	D_0	
DZ40Y–100L	25	210	135	100	78	58	24	4–ϕ18	365	200	18
	32	230	150	110	82	66	24	4–ϕ23	420	240	27
	50	250	195	145	112	88	28	4–ϕ25	630	360	45
	65	280	220	170	138	110	32	8–ϕ25	700	400	60
	80	310	230	180	148	121	34	8–ϕ25	760	400	76
	100	350	265	210	172	150	38	8–ϕ30	900	400	128





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN1.6/2.5MPa								WT (kg)
		L	D	D_1	D_2	b	Z-φd	H	D_0	
BZ41H-16C BZ41W-16P BZ41W-16R	40	200	160	125	100	18	4-φ18	310	200	49
	50	250	180	145	120	18	4-φ18	358	240	54
	65	265	195	160	135	20	4-φ18	373	240	81
	80	280	215	180	155	20	8-φ18	435	280	100
	100	300	245	210	185	22	8-φ18	500	300	120
	125	325	280	240	210	24	8-φ23	614	320	210
	150	350	335	295	265	26	12-φ23	674	360	260
	200	400	405	355	320	30	12-φ25	818	400	300
	250	450	460	410	375	30	12-φ25	969	450	400
	300	500	520	470	435	34	16-φ25	1145	560	490
BZ41H-25 BZ41W-25P BZ41W-25R	40	200	160	125	100	20	4-φ18	358	240	52
	50	250	180	145	120	22	4-φ18	373	240	56
	65	265	195	160	135	22	8-φ18	435	280	86
	80	280	230	190	160	24	8-φ18	500	300	105
	100	300	270	220	188	28	8-φ23	614	320	170
	125	350	300	250	218	30	8-φ25	674	360	245
	150	350	360	310	278	34	12-φ25	818	400	270
	200	400	425	370	332	36	12-φ30	969	450	380
	250	450	485	430	390	40	12-φ30	1145	560	535
	300	500	550	490	448	44	16-φ34	1145	640	546

主要特点

全通径，全封闭，明杆带支架
中法兰螺栓连接
刚性闸板，导流孔设计
阀杆升降，手轮不升降
伞齿轮操作选配
标准法兰连接
对焊连接





CHIEF FEATURES

FULL PORT, OUTSIDE SCREW AND YOKE(OS&Y)
BOLTE D BONNET
SOLID WEDGE,THRO-CONDUIT DESIGN
RISING STEM AND NON-RISING HANDWHEEL
AVAILABLE WITH GEAR OPERATOR
FLANGED ENDS
BUTT-WELDING ENDS

产品规范Product Specification

产品规范 Product Specification	设计规范 Design Spec.	结构长度 Face to Face	连接法兰 Flange End	试验与检验 Test &Check	压力-温度 Pressure-Temp.	产品标识 Marking	供货规范 Supply
	JB/T 5298	JB/T 5298	JB/T 79	JB/T 5298	Gb9131	GB/T 12220	JB/T 7928
	API 6D	API 6D	ANSI B16.5	API 6D	ANSI B16.34	Mss sp-25	API 6D

主要零部件材料Main Part Material

零件名称	零部件材料Part material				Part Name
	JB/T 7298		API 6D		
阀门/阀盖	WCB	WCB	A352-LCB	A352-CF8M	Body/Bonnet
阀　板	2Cr13+ENP	20CrMoV+STL	ANS1410+ENP	ANSI316+ENP	Wedge
阀　杆	2Cr13	2Cr13	A182-F6a	A182-F316S	Stem
阀　座	25+PTEF	20CrMoV+STL	A105+PTFE	A182-F316+PTFE	Seat
填　料	NBR/FPM	柔性石墨/Flexible Graphite		聚四氟乙烯/PTFE+FPM	Packing
垫　片	18-8/柔性石墨/18-8Flexible Graphite				Gasket
螺　栓	35	35CrMo	3A193-B7M	A193-B8	Bolt
适用温度	-29～250℃	-29～550℃	-46～350℃	-40～200℃	Suitable Temp.
适用介质	水、油品、蒸汽 Water、Oil、Steam	水、油品、蒸汽 Water、Oil、Steam	丙烷、乙烯 Steam、Oil	硝酸类 Nitric Acid	Suitable Medium





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN1.0MPa										WT(kg)	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2	D_0	110	112
Z43WF-10C Z43F-10C Z43WY-10C Z43Y-10C KZ43WF-10C KZ43F-10C Z47WF-10C Z47F-10C	50	178	165	125	99	20	4-φ18	475	80	122	250	23	25
	65	190	185	145	118	20	4-φ18	535	90	152	300	40	45
	80	203	200	160	132	20	8-φ18	600	100	178	300	45	50
	100	229	220	180	156	22	8-φ18	700	110	220	300	52	57
	125	254	250	210	184	22	8-φ18	790	130	255	350	95	105
	150	267	285	240	211	24	8-φ22	910	145	345	350	105	115
	200	292	340	295	266	26	8-φ22	1095	170	420	350	140	155
	250	330	395	350	319	26	12-φ22	1370	210	495	400	240	265
	300	356	445	400	370	26	12-φ22	1470	240	600	450	300	330
	350	381	505	460	429	26	16-φ22	1730	265	640	450	460	506
	400	406	565	515	480	28	16-φ22	1870	290	720	500	560	620
	450	432	615	565	530	28	20-φ26	2185	325	798	500	780	860
	500	457	670	620	582	34	20-φ26	2335	360	875	600	1050	1160
	600	508	780	725	682	34	20-φ30	2680	425	1170	800	1680	1850
	700	610	895	840	794	34	24-φ30	3080	455	1250	800	2250	2480
	800	660	1015	950	901	36	24-φ33	3490	505	1370	1000	3180	3500
	900	711	1115	1050	1001	38	28-φ33	3900	545	1500	1000	4260	4690
	1000	811	1230	1160	1112	38	28-φ36	4320	610	1670	1000	5540	6100

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	PN1.6MPa										WT(kg)	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2	D_0	110	112
Z43WF-16C Z43F-16C Z43WY-16C Z43Y-16C KZ43WF-16C KZ43F-16C Z47WF-16C Z47F-16C	50	178	160	125	100	16	4-φ18	475	80	122	250	23	25
	65	190	180	145	120	18	4-φ18	535	90	152	300	40	45
	80	203	195	160	135	20	8-φ18	600	100	178	300	45	50
	100	229	215	180	155	20	8-φ18	700	110	220	300	52	57
	125	254	245	210	185	22	8-φ18	790	130	255	350	95	105
	150	267	280	240	210	24	8-φ23	910	145	345	350	105	115
	200	292	335	295	265	26	12-φ23	1095	170	420	350	140	155
	250	330	405	355	320	30	12-φ25	1370	210	495	400	240	265
	300	356	460	410	375	30	12-φ25	1470	240	600	450	300	330
	350	381	520	470	435	34	16-φ25	1730	265	640	450	460	506
	400	406	580	525	485	36	16-φ30	1870	290	720	500	560	620
	450	432	640	585	545	40	20-φ30	2185	325	798	500	780	860
	500	457	705	650	608	44	20-φ34	2335	360	875	600	1050	1160
	600	508	840	770	718	48	20-φ41	2680	425	1170	800	1680	1850
	700	610	910	840	788	50	24-φ41	3080	455	1250	800	2250	2480
	800	660	1020	950	898	52	24-φ41	3490	505	1370	1000	3180	3500
	900	711	1120	1050	998	54	28-φ41	3900	545	1500	1000	4260	4690
	1000	811	1255	1170	1110	56	28-φ48	4320	610	1670	1000	5540	6100

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN2.5MPa										WT(kg)	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2	D_0	110	112
Z43WF-25 Z43F-25 Z43WY-25 Z43Y-25 KZ43WF-25 KZ43F-25 Z47WF-25 Z47F-25	50	178	160	125	100	20	4-φ18	475	80	122	250	25	27
	65	190	180	145	120	22	8-φ18	535	90	152	300	45	49
	80	203	195	160	135	22	8-φ18	600	100	178	300	50	55
	100	229	230	190	160	24	8-φ23	700	110	220	300	60	66
	125	254	270	220	188	28	8-φ25	790	130	255	350	110	121
	150	267	300	250	218	30	8-φ25	910	145	345	350	128	140
	200	292	360	310	280	34	12-φ25	1095	170	420	350	165	181
	250	330	425	370	332	36	12-φ30	1370	210	495	400	280	310
	300	356	485	430	390	40	16-φ30	1470	240	600	450	370	410
	350	381	550	490	448	44	16-φ34	1730	265	640	450	525	580
	400	406	610	550	505	48	16-φ34	1870	290	720	500	635	700
	450	432	660	600	555	50	20-φ34	2185	325	798	500	1010	1110
	500	457	760	660	610	52	20-φ41	2335	360	875	600	1280	1410
	600	508	840	770	718	56	20-φ41	2680	425	1170	800	1930	2120
	700	610	955	875	815	60	24-φ48	3080	455	1250	800	3010	3310
	800	660	1070	990	930	64	24-φ48	3490	505	1370	1000	3820	4200
	900	711	1180	1090	1025	66	28-φ54	3900	545	1500	1000	5120	5630
	1000	811	1305	1210	1140	66	28-φ58	4320	610	1670	1000	6400	7040

总机：021-59546368



主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0MPa										WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	100	112
Z43WF-40 Z43F-40 Z43WY-40 Z43Y-40 KZ43WF-40 KZ43F-40 Z47WF-40 Z47F-40	50	216	160	125	100	88	20	4-φ18	475	80	122	250	38	42
	65	241	180	145	120	110	22	8-φ18	535	90	152	300	57	62
	80	283	195	160	135	121	22	8-φ18	600	100	178	300	68	75
	100	305	230	190	160	150	24	8-φ23	700	110	220	300	75	82
	125	381	270	220	188	176	28	8-φ25	790	130	255	350	133	146
	150	403	300	250	218	204	30	8-φ25	910	145	345	350	165	180
	200	419	375	320	282	260	38	12-φ30	1095	170	420	350	315	350
	250	457	445	385	345	313	42	12-φ34	1370	210	495	400	410	450
	300	502	510	450	408	364	46	16-φ34	1470	240	600	450	620	685
	350	762	570	510	465	422	52	16-φ34	1730	265	640	450	870	950
	400	838	655	585	535	474	58	16-φ41	1870	290	720	500	1370	1460
	450	914	680	610	560	524	60	20-φ41	2185	325	798	500	1632	1680
	500	991	755	670	612	576	62	20-φ48	2335	360	875	600	2050	2370
	600	1143	890	795	730	678	62	20-φ54	2680	425	1170	800	3110	3405

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN6.4MPa										WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z43WF-64 Z43F-64 Z43WY-64 Z43Y-64 KZ43WF-64 KZ43F-64 Z47WF-64 Z47F-64	50	250	175	135	105	88	26	4-φ23	485	108	158	300	55	90
	65	280	200	160	130	110	28	8-φ23	550	125	190	300	72	80
	80	310	210	170	140	121	30	8-φ23	650	145	225	350	85	93
	100	350	250	200	168	150	32	8-φ25	760	165	245	350	98	110
	125	400	295	240	202	176	36	8-φ30	860	190	275	400	164	180
	150	450	340	280	240	204	38	8-φ34	970	220	330	400	205	225
	200	550	405	345	300	260	44	12-φ34	1150	280	410	500	350	385
	250	650	470	400	352	313	48	12-φ41	1400	330	490	500	490	540
	300	750	530	460	412	364	54	16-φ41	1580	380	570	600	760	840
	350	850	595	525	475	422	60	16-φ41	1750	410	770	600	991	1135
	400	950	670	585	525	474	66	16-φ48	1890	470	882	800	1510	1670
	450	1050	670	630	570	524	70	20-φ48	2210	560	1015	800	1830	1980
	500	1150	800	705	640	576	70	20-φ54	2365	595	1115	1000	1640	2930
	600	1350	930	820	750	678	76	20-φ58	2840	640	1265	1000	4280	4720

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN10.0MPa										WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z43WF-100 Z43F-100 Z43WY-100 Z43Y-100 KZ43WF-100 KZ43F-100 Z47WF-100 Z47F-100	50	250	175	135	105	88	26	4-φ23	485	108	158	300	55	90
	65	280	200	160	130	110	28	8-φ23	550	125	190	300	72	80
	80	310	210	170	140	121	30	8-φ23	650	145	225	350	85	93
	100	350	250	200	168	150	32	8-φ25	760	165	245	350	98	110
	125	400	295	240	202	176	36	8-φ30	860	190	275	400	164	180
	150	450	340	280	240	204	38	8-φ34	970	220	330	400	205	225
	200	550	405	345	300	260	44	12-φ34	1150	280	410	500	350	385
	250	650	470	400	352	313	48	12-φ41	1400	330	490	500	490	540
	300	750	530	460	412	364	54	16-φ41	1580	380	570	600	760	840
	350	850	595	525	475	422	60	16-φ41	1750	410	770	600	991	1135
	400	950	670	585	525	474	66	16-φ48	1890	470	882	800	1510	1670
	450	1050	670	630	570	524	70	20-φ48	2210	560	1015	800	1830	1980
	500	1150	800	705	640	576	70	20-φ54	2365	595	1115	1000	1640	2930
	600	1350	930	820	750	678	76	20-φ58	2840	640	1265	1000	4280	4720

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN15.0MPa										WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z43WF-150 Z43F-150 Z43WY-150 Z43Y-150 KZ43WF-150 KZ43F-150 Z47WF-150 Z47F-150	50	368	215	165	132	88	36	8-φ25	485	108	158	300	81	90
	65	419	245	190	152	110	44	8-φ30	570	125	190	300	115	125
	80	381	260	205	168	121	46	8-φ30	650	145	225	350	155	170
	100	457	300	240	200	150	48	8-φ34	760	165	245	350	200	220
	125	525	355	285	238	176	60	8-φ41	860	190	275	400	345	375
	150	610	390	318	270	204	66	12-φ41	970	220	330	400	600	650
	200	737	480	400	345	260	78	12-φ48	1150	280	410	500	780	840
	250	838	580	485	425	313	88	12-φ54	1420	330	490	500	1060	1120
	300	965	665	570	510	364	100	16-φ54	1595	380	570	600	1280	1390
	350	1029	640	559	424	414.5	86	20-φ42	1830	410	770	600	1510	1705
	400	1130	705	616	481	471.5	89	20-φ45	2050	470	882	800	2230	2385
	450	1219	785	686	544	535	102	20-φ51	2410	560	1015	800	2410	2550
	500	1321	855	749.5	595	586	108	20-φ55	1650	595	1115	1000	3200	3410
	600	1549	1040	901.5	703.5	694	140	20-φ68	3090	640	1265	1000	4890	5010

总机：021-59546368





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN1.0MPa										WT（kg）	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2	D_0	110	112
Z543WF-10C Z543F-10C Z543WY-10C Z543Y-10C KZ543WF-10C KZ543F-10C Z547WF-10C Z547W-10C	100	229	220	180	156	22	8-φ18	770	110	220	BA-0	87	94
	125	254	250	210	184	22	8-φ18	870	130	255	BA-0	130	140
	150	267	285	240	211	24	8-φ22	965	145	345	BA-0	140	151
	200	292	340	295	266	24	8-φ22	1200	170	420	BA-0	175	200
	250	330	395	350	319	26	12-φ22	1360	210	495	BA-0	275	300
	300	356	445	400	370	26	12-φ22	1560	240	600	BA-1	350	380
	350	381	505	460	429	26	16-φ22	1740	265	640	BA-1	510	550
	400	406	565	515	480	26	12-φ26	1930	290	720	BA-1	610	660
	450	432	615	565	530	28	20-φ26	2160	325	798	BA-1	830	900
	500	457	670	620	582	28	20-φ26	2420	360	875	BA-2	1150	1240
	600	508	780	725	682	34	20-φ30	2800	425	1170	BA-2	1780	1922
	700	610	895	840	794	34	24-φ30	3200	455	1250	BA-2	2350	2530
	800	660	1015	950	901	36	24-φ33	3640	505	1370	BA-3	3380	3650
	900	711	1115	1050	1001	38	28-φ33	4050	545	1500	BA-3	4460	4820
	1000	811	1230	1160	1112	38	28-φ36	4470	610	1670	BA-3	5740	6200

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	PN1.6MPa										WT(kg)	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2	D_0	110	112
Z543WF-16C Z543F-16C Z543WY-16C Z543Y-16C KZ543WF-16C KZ543F-16C Z547WF-16C Z547W-16C	100	229	215	180	155	20	8-φ18	770	110	220	BA-0	87	94
	125	254	245	210	185	22	8-φ18	870	130	255	BA-0	130	140
	150	267	280	240	210	24	8-φ23	965	145	345	BA-0	140	151
	200	292	335	295	265	26	12-φ23	1200	170	420	BA-0	175	200
	250	330	405	355	320	30	12-φ25	1360	210	495	BA-0	275	300
	300	356	460	410	375	30	12-φ25	1560	240	600	BA-1	350	380
	350	381	520	470	435	34	16-φ25	1740	265	640	BA-1	510	550
	400	406	580	525	485	36	16-φ30	1930	290	720	BA-1	610	660
	450	432	640	585	545	40	20-φ30	2160	325	798	BA-1	830	900
	500	457	705	650	608	44	20-φ34	2420	360	875	BA-2	1150	1240
	600	508	840	770	718	48	20-φ41	2800	425	1170	BA-2	1780	1922
	700	610	910	840	788	50	24-φ41	3200	455	1250	BA-2	2350	2530
	800	660	1020	950	898	52	24-φ41	3640	505	1370	BA-3	3380	3650
	900	711	1120	1050	998	54	28-φ41	4050	545	1500	BA-3	4460	4820
	1000	811	1255	1170	1110	56	28-φ48	4470	610	1670	BA-3	5740	6200

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN2.5MPa										WT(kg)	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2	D_0	110	112
Z543WF-25 Z543F-25 Z543WY-25 Z543Y-25 KZ543WF-25 KZ543F-25 Z547WF-25 Z547W-25	100	229	230	190	160	24	8-φ23	770	110	220	BA-0	95	103
	125	254	270	220	188	28	8-φ25	870	130	255	BA-0	145	156
	150	267	300	250	218	30	8-φ25	965	145	345	BA-0	163	176
	200	292	360	310	278	34	12-φ25	1200	170	420	BA-0	200	216
	250	330	425	370	332	36	12-φ30	1360	210	495	BA-0	330	360
	300	356	485	430	390	40	16-φ30	1560	240	600	BA-1	420	450
	350	381	550	490	448	44	16-φ34	1740	265	640	BA-1	575	620
	400	406	610	550	505	48	16-φ34	1930	290	720	BA-1	735	795
	450	432	660	600	555	50	20-φ34	2160	325	798	BA-1	1110	1200
	500	457	730	660	610	52	20-φ41	2420	360	875	BA-2	1380	1490
	600	508	840	770	718	56	20-φ41	2800	425	1170	BA-2	2030	2192
	700	610	955	875	815	60	24-φ48	3200	455	1250	BA-2	3210	3500
	800	660	1070	990	930	64	24-φ48	3640	505	1370	BA-3	4020	4340
	900	711	1180	1090	1025	66	28-φ54	4050	545	1500	BA-3	5320	5750
	1000	811	1305	1210	1140	68	28-φ58	4470	610	1670	BA-3	6600	7130

总机：021-59546368



主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0MPa										WT（kg）	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2	D_0	110	112
Z543WF-40 Z543F-40 Z543WY-40 Z543Y-40 KZ543WF-40 KZ543F-40 Z547WF-40 Z547W-40	100	305	230	190	160	24	8-φ23	770	110	220	BA-0	110	118
	125	381	270	220	188	28	8-φ25	870	130	255	BA-0	170	181
	150	403	300	250	218	30	8-φ25	970	145	345	BA-0	200	215
	200	419	375	320	282	38	12-φ30	1200	170	420	BA-0	350	380
	250	457	445	385	345	42	12-φ34	1370	210	495	BA-0	460	500
	300	502	510	450	408	46	16-φ34	1560	240	600	BA-1	670	725
	350	762	570	510	465	52	16-φ34	1740	265	640	BA-1	870	940
	400	838	655	585	535	58	16-φ41	1970	290	720	BA-1	1390	1500
	450	914	680	610	560	60	20-φ41	2260	325	798	BA-1	1662	1750
	500	991	755	670	612	62	20-φ48	2420	360	875	BA-2	2337	2515
	600	1143	890	795	730	62	20-φ54	2800	425	1170	BA-2	3940	4290
	700	1346	995	900	835	68	24-φ54	3230	455	1250	BA-2	4140	4470
	800	1524	1135	1030	960	76	24-φ58	3640	505	1370	BA-3	5550	6000
	900	1727	1172	1089	1032	85	32-φ45	4050	545	1500	BA-3	6100	6610

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN6.4MPa											WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z543WF-64 Z543F-64 Z543WY-64 Z543Y-64 KZ543WF-64 KZ543F-64 Z547WF-64 Z547W-64	80	310	210	170	140	121	30	8-φ23	750	145	225	BA-0	85	93
	100	350	250	200	168	150	32	8-φ25	860	165	245	BA-0	98	110
	125	400	295	240	202	176	36	8-φ30	960	190	275	BA-0	164	180
	150	450	340	280	240	204	38	8-φ34	1096	220	330	BA-1	205	225
	200	550	405	345	300	260	44	12-φ34	1290	280	410	BA-1	350	385
	250	650	470	400	352	313	48	12-φ41	1580	330	490	BA-1	490	540
	300	750	530	460	412	346	54	16-φ41	1705	380	570	BA-2	760	840
	350	850	595	525	475	422	60	16-φ41	1977	410	770	BA-2	991	1135
	400	950	670	585	525	474	66	16-φ48	2125	470	882	BA-2	1510	1670
	450	1050	670	630	570	524	70	20-φ48	2525	560	1015	BA-2	1830	1980
	500	1150	800	705	640	576	70	20-φ54	2682	595	1115	BA-3	2640	2930
	600	1350	930	820	750	678	76	20-φ58	3186	640	1265	BA-3	4280	4720

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	PN10.0MPa											WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z543WF-100 Z543F-100 Z543WY-100 Z543Y-100 KZ543WF-100 KZ543F-100 Z547WF-100 Z547W-100	80	354	230	180	148	121	34	8-φ25	750	145	225	BA-0	135	145
	100	432	265	210	172	150	38	8-φ30	860	165	245	BA-0	172	185
	125	508	310	250	210	176	42	8-φ34	960	190	275	BA-1	235	255
	150	559	350	290	250	204	46	12-φ34	1096	220	330	BA-1	340	265
	200	660	430	360	312	260	54	12-φ41	1290	280	410	BA-1	445	480
	250	787	500	430	382	313	60	12-φ41	1580	330	490	BA-2	670	725
	300	838	585	500	442	364	70	16-φ48	1705	380	570	BA-2	1190	1290
	350	889	655	560	498	422	76	16-φ54	1977	410	770	BA-2	1800	1950
	400	991	715	620	558	474	80	16-φ54	2125	470	882	BA-3	2470	2260
	450	1092	770	675	615	524	84	16-φ58	2525	560	1015	BA-3	2740	3050
	500	1194	870	760	690	576	90	20-φ58	2682	595	1115	BA-3	3370	3640
	600	1397	990	875	800	678	95	24-φ58	3186	640	1265	BA-3	4640	4870


主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN15.0MPa											WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z543WF-150 Z543F-150 Z543WY-150 Z543Y-150 KZ543WF-150 KZ543F-150 Z547WF-150 Z547W-150	50	368	215	165	132	88	36	8-φ25	525	108	158	BA-0	116	125
	65	419	245	190	152	110	44	8-φ30	615	125	190	BA-0	140	151
	80	381	260	205	168	121	46	8-φ30	778	145	225	BA-0	190	205
	100	457	300	240	200	150	48	8-φ34	890	165	245	BA-1	250	270
	125	525	355	285	238	176	60	8-φ41	1010	190	275	BA-1	385	426
	150	610	390	318	270	204	66	12-φ41	1290	220	330	BA-1	650	700
	200	737	480	400	345	260	78	12-φ48	1480	280	410	BA-2	880	950
	250	838	580	485	425	313	88	12-φ54	1670	330	490	BA-2	1160	1250
	300	965	665	570	510	364	100	16-φ54	1880	380	570	BA-2	1380	1490
	350	1029	640	559	424	414.5	86	20-φ42	2105	410	770	BA-3	1510	2100
	400	1130	705	616	481	471.5	89	20-φ45	2410	470	882	BA-3	2230	2910
	450	1219	785	686	544	535	102	20-φ51	2550	560	1015	BA-3	2410	3140
	500	1321	855	749.5	595	586	108	20-φ55	2950	595	1115	BA-3X	3200	3870
	600	1549	1040	901.5	703.5	694	140	20-φ68	3210	640	1265	BA-3X	4890	5020

总机：021-59546368





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN1.0MPa										WT(kg)	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2	D_0	110	112
Z6s43WF-10C Z6s43F-10C Z6s43WY-10C Z6s43Y-10C KZ6s43WF-10C KZ6s43F-10C Z7s43WF-10C Z7s43F-10C KZ7s43WF-10C KZ7s43F-10C Z6s47WF-10C Z6s47F-10C	50	178	165	125	99	20	4-φ18	525	80	122	250	33	35
	65	190	185	145	118	20	4-φ18	650	90	152	300	56	62
	80	203	200	160	132	20	8-φ18	730	100	178	300	63	69
	100	229	220	180	156	22	8-φ18	850	110	220	300	73	80
	125	254	250	210	184	22	8-φ18	985	130	255	350	133	146
	150	267	285	240	211	24	8-φ22	1120	145	345	350	147	161
	200	292	340	295	266	26	8-φ22	1430	170	420	350	196	216
	250	330	395	350	319	26	12-φ22	1670	210	495	400	340	370
	300	356	445	400	370	26	12-φ22	1930	240	600	450	420	462
	350	381	505	460	429	26	16-φ22	2190	265	640	450	645	710
	400	406	565	515	480	28	16-φ22	2450	290	720	500	785	860
	450	432	615	565	530	28	20-φ26	2760	325	798	500	1090	1205
	500	457	670	620	582	34	20-φ26	3050	360	875	600	1470	1620
	600	508	780	725	682	34	20-φ30	3580	425	1170	800	2350	2890
	700	610	895	840	794	34	24-φ30	4130	455	1250	800	3150	3470
	800	660	1015	950	901	36	24-φ33	4520	505	1370	1000	3840	4020
	900	711	1115	1050	1001	38	28-φ33	5570	545	1500	1000	5360	5540
	1000	811	1230	1160	1112	38	28-φ36	5790	610	1670	1000	6750	6910

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	PN1.6MPa										WT(kg)	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2	D_0	110	112
Z6s43WF-16C Z6s43F-16C	50	178	160	125	100	16	4-φ18	525	80	122	250	35	38
	65	190	180	145	120	18	4-φ18	650	90	152	300	60	65
	80	203	195	160	135	20	4-φ18	730	100	178	300	67	73
	100	229	215	180	155	20	8-φ18	850	110	220	300	77	84
Z6s43WY-16C Z6s43Y-16C	125	254	245	210	185	22	8-φ18	985	130	255	350	140	154
	150	267	280	240	210	24	8-φ18	1120	145	345	350	161	176
	200	292	335	295	265	26	8-φ23	1430	170	420	350	210	230
KZ6s43WF-16C KZ6s43F-16C	250	330	405	355	320	30	12-φ23	1670	210	495	400	365	400
	300	356	460	410	375	30	12-φ25	1930	240	600	450	490	540
Z7s43WF-16C Z7s43F-16C	350	381	520	470	435	34	12-φ25	2190	265	640	450	700	700
	400	406	580	525	485	36	16-φ30	2450	290	720	500	855	940
	450	432	640	585	545	40	16-φ30	2760	325	798	500	1360	1495
KZ7s43WF-16C KZ7s43F-16C	500	457	705	650	608	44	20-φ34	3050	360	875	600	1680	1850
	600	508	840	770	718	48	20-φ41	3580	425	1170	800	2590	2850
Z6s47WF-16C Z6s47F-16C	700	610	910	840	788	50	24-φ41	4130	455	1250	800	4075	4481
	800	660	1020	950	898	52	24-φ41	4520	505	1370	1000	4260	4570
	900	711	1120	1050	998	54	24-φ41	5570	545	1500	1000	5710	5930
	1000	811	1255	1170	1110	56	28-φ48	5790	610	1670	1000	6980	7110


主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN2.5MPa										WT(kg)	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2	D_0	110	112
Z6s43WF-25 Z6s43F-25	50	178	160	125	100	20	4-φ18	525	80	122	250	35	38
	65	190	180	145	120	22	8-φ18	650	90	152	300	63	68
	80	203	195	160	135	22	8-φ18	730	100	178	300	74	77
	100	229	215	190	160	24	8-φ23	850	110	220	300	84	93
Z6s43WY-25 Z6s43Y-25	125	254	245	220	188	28	8-φ25	985	130	255	350	154	170
	150	267	280	250	218	30	8-φ25	1120	145	345	350	180	196
	200	292	335	310	278	34	12-φ25	1430	170	420	350	230	258
KZ6s43WF-25 KZ6s43F-25	250	330	405	370	332	36	12-φ30	1670	210	495	400	395	430
	300	356	460	430	390	40	16-φ30	1930	240	600	450	520	570
Z7s43WF-25 Z7s43F-25	350	381	520	490	448	44	16-φ34	2190	265	640	450	735	810
	400	406	580	550	505	48	16-φ34	2450	290	720	500	890	980
	450	432	640	600	550	50	20-φ34	2760	325	798	500	1415	1555
KZ7s43WF-25 KZ7s43F-25	500	457	705	660	610	52	20-φ41	3050	360	875	600	1975	2270
	600	508	840	770	718	56	20-φ41	3580	425	1170	800	2700	2975
Z6s47WF-25 Z6s47F-25	700	610	955	875	815	60	24-φ48	4130	455	1250	800	4215	4635
	800	660	1070	990	930	64	24-φ48	4520	505	1370	1000	4440	4830
	900	711	1180	1090	1025	66	28-φ54	5570	545	1500	1000	5970	6350
	1000	811	1305	1210	1140	68	28-φ58	5790	610	1670	1000	6210	6730

总机：021-59546368





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0MPa										WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z6s43WF-40 Z6s43F-40 Z6s43WY-40 Z6s43Y-40 KZ6s43WF-40 KZ6s43F-40 Z7s43WF-40 Z7s43F-40 KZ7s43WF-40 KZ7s43F-40 Z6s47WF-40 Z6s47F-40	50	216	160	125	100	88	20	4-φ18	525	80	122	250	38	42
	65	241	180	145	120	110	22	8-φ18	650	90	152	300	63	68
	80	283	195	160	135	121	22	8-φ18	730	100	178	300	75	88
	100	305	230	190	160	150	24	8-φ23	850	110	220	300	95	105
	125	381	270	220	188	176	28	8-φ25	985	130	255	350	186	220
	150	403	300	250	218	204	30	8-φ25	1120	145	345	350	231	245
	200	419	375	320	282	260	38	12-φ30	1430	170	420	350	285	320
	250	457	445	385	345	313	42	12-φ34	1670	210	495	400	440	495
	300	502	510	450	408	364	46	16-φ34	1930	240	600	450	575	630
	350	762	570	510	465	422	52	16-φ34	2190	265	640	450	870	940
	400	838	655	585	535	474	58	16-φ41	2450	290	720	500	1150	1230
	450	914	680	610	560	524	60	20-φ41	2760	325	798	500	1810	1850
	500	991	755	670	612	576	62	20-φ48	3050	360	875	600	2130	2460
	600	1143	890	795	730	678	62	20-φ54	3580	425	1170	800	2930	3270
	700	1346	995	900	835	768	68	24-φ54	4130	455	1250	800	4420	4910
	800	1524	1135	1030	960	876	76	24-φ58	4520	505	1370	1000	4780	5105
	900	1727	1172	1089	1032	976	85	32-φ45	5570	545	1500	1000	6330	6660

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN6.4MPa											WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z6s43WF-64 Z6s43F-64	50	250	175	135	105	88	26	4-φ23	533	108	158	300	83	88
	65	280	200	160	130	110	28	8-φ23	653	125	190	300	125	125
	80	310	210	170	140	121	30	8-φ23	735	145	225	350	140	155
Z6s43WY-64 Z6s43Y-64	100	350	250	200	168	150	32	8-φ25	860	165	245	350	220	180
	125	400	295	240	202	176	36	8-φ30	985	190	275	400	260	290
KZ6s43WF-64 KZ6s43F-64	150	450	340	280	240	204	38	8-φ34	1125	220	330	400	450	360
	200	550	405	345	300	260	44	12-φ34	1435	280	410	500	595	750
Z7s43WF-64 Z7s43F-64	250	650	470	400	352	313	48	12-φ41	1780	330	490	500	870	1150
	300	750	530	460	412	364	54	16-φ41	2030	380	570	600	1310	1840
KZ7s43WF-64 KZ7s43F-64	350	850	595	525	475	422	60	16-φ41	2305	410	770	600	1790	2130
	400	950	670	585	525	474	66	16-φ48	2560	470	882	800	2210	2670
Z6s47WF-64 Z6s47F-64	450	1050	670	630	570	524	70	20-φ48	2835	560	1015	800	2630	2890
	500	1150	800	705	640	576	70	20-φ54	3120	595	1115	1000	3080	3320
	600	1350	930	820	750	678	76	20-φ58	3350	640	1265	1000	4470	4720

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	PN10.0MPa											WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z6s43WF-100 Z6s43F-100	50	292	195	145	112	88	28	4-φ25	543	108	158	300	83	98
	65	330	220	170	138	110	32	8-φ25	663	125	190	300	120	140
	80	356	230	180	148	121	34	8-φ25	745	145	225	350	137	155
Z6s43WY-100 Z6s43Y-100	100	432	265	210	172	150	38	8-φ30	870	165	245	350	171	210
	125	508	310	250	210	176	42	8-φ34	995	190	275	400	260	288
KZ6s43WF-100 KZ6s43F-100	150	559	350	290	250	204	46	12-φ34	1135	220	330	400	405	456
	200	660	430	360	312	260	54	12-φ41	1445	280	410	500	695	765
Z7s43WF-100 Z7s43F-100	250	787	500	430	382	313	60	16-φ41	1790	330	490	500	800	960
	300	838	585	500	442	364	70	16-φ48	2040	380	570	600	1290	1390
KZ7s43WF-100 KZ7s43F-100	350	889	655	560	498	422	76	16-φ54	2410	410	770	600	2140	2480
	400	991	715	620	558	474	80	16-φ54	2760	470	882	800	2685	2975
	450	1092	770	675	615	524	84	16-φ58	3040	560	1015	800	2975	3120
	500	1194	870	760	690	576	90	20-φ58	3318	595	1115	1000	3750	3950
	600	1397	990	875	800	678	95	24-φ58	4080	640	1265	1000	5420	5720

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN15.0MPa											WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z6s43WF-150 Z6s43F-150	50	368	215	165	132	88	36	8-φ25	550	108	158	300	141	165
	65	419	245	190	152	110	44	8-φ30	670	125	190	300	165	186
	80	381	260	205	168	121	46	8-φ30	750	145	225	350	227	253
Z6s43WY-150 Z6s43Y-150	100	457	300	240	200	150	48	8-φ34	875	165	245	350	286	312
	125	525	355	285	238	176	60	8-φ41	1000	190	275	400	485	520
KZ6s43WF-150 KZ6s43F-150	150	610	390	318	270	204	66	12-φ41	1140	220	330	400	840	900
	200	737	480	400	345	260	78	12-φ48	1450	280	410	500	1095	1205
Z7s43WF-150 Z7s43F-150	250	838	580	485	425	313	88	12-φ54	1790	330	490	500	1490	1680
	300	965	665	570	510	364	110	16-φ54	2045	380	570	600	1800	2025
KZ7s43WF-150 KZ7s43F-150	350	1029	640	559	424	414.5	86	20-φ42	2510	410	770	600	2030	2225
	400	1130	705	616	481	471.5	89	20-φ45	2680	470	882	800	2460	2680
	450	1219	785	686	544	535	102	20-φ51	2880	560	1015	800	2660	2890
	500	1321	855	249.5	595	586	108	20-φ55	3230	595	1115	1000	3490	3770
	600	1549	1040	901.5	703.5	694	140	20-φ68	3510	640	1265	1000	5020	5350

总机：021-59546368



主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN1.0MPa									选配电装 E.A	WT（kg）	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2		110	120
Z9B43WF-10C Z9B43F-10C Z9B43WY-10C Z9B43Y-10C KZ9B43WF-10C KZ9B43F-10C Z9B47WF-10C Z9B47F-10C	50	178	165	125	99	20	4-φ18	620	80	122	SMC-04	55	58
	65	190	185	145	118	20	4-φ18	710	90	152	SMC-04	75	80
	80	203	200	160	132	20	8-φ18	785	100	178	SMC-04	86	92
	100	229	220	180	156	22	8-φ18	910	110	220	SMC-04	97	104
	125	254	250	210	184	22	8-φ18	1010	130	255	SMC-03	140	150
	150	267	285	240	211	24	8-φ18	1120	145	345	SMC-03	150	161
	200	292	340	295	266	24	8-φ22	1390	170	420	SMC-00	210	233
	250	330	395	350	319	26	12-φ22	1550	210	495	SMC-00	240	332
	300	356	445	400	370	26	16-φ22	1740	240	600	SMC-00	370	400
	350	381	505	460	429	26	16-φ22	1915	265	640	SMC-0	570	610
	400	406	565	515	480	26	12-φ26	2105	290	720	SMC-0	670	720
	450	432	615	565	530	28	20-φ26	2370	325	798	SMC-0	930	1000
	500	457	670	620	582	28	20-φ26	2590	360	875	SMC-1	1200	1290
	600	508	780	725	682	34	20-φ30	2990	425	1170	SMC-1	1860	2000
	700	610	895	840	794	34	24-φ30	3390	455	1250	SMC-1	2430	2610
	800	660	1015	950	901	36	24-φ33	3850	505	1370	SMC-2	3300	3660
	900	711	1115	1050	1001	38	28-φ33	4260	545	1500	SMC-2	4470	4830
	1000	811	1230	1160	1112	38	28-φ36	4680	610	1670	SMC-2	5750	6210

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	PN1.6MPa									选配电装 E.A	WT(kg)	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2		110	120
	50	178	160	125	100	16	4-φ18	620	80	122	SMC-04	58	64
	65	190	180	145	120	18	4-φ18	710	90	152	SMC-04	78	87
	80	203	195	160	135	20	8-φ18	785	100	178	SMC-04	88	95
	100	229	215	180	155	20	8-φ18	910	110	220	SMC-04	100	107
Z9B43WF-16C	125	254	245	210	185	20	8-φ18	1010	130	255	SMC-03	145	155
Z9B43F-16C	150	267	280	240	210	24	8-φ23	1120	145	345	SMC-03	160	172
	200	292	335	295	265	36	12-φ23	1390	170	420	SMC-000	220	235
Z9B43WF-16C	250	330	405	335	320	30	12-φ25	1550	210	495	SMC-00	330	353
Z9B43Y-16C	300	356	460	410	375	30	12-φ25	1740	240	600	SMC-00	420	452
	350	381	520	470	435	34	16-φ25	1915	265	640	SMC-0	610	456
KZ9B43WF-16C	400	406	580	525	485	36	16-φ30	2105	290	720	SMC-0	720	775
KZ9B43F-16C	450	432	640	585	545	40	20-φ30	2370	325	798	SMC-0	1130	1200
Z9B47WF-16C	500	457	705	650	608	44	20-φ34	2590	360	875	SMC-1	1350	1450
Z9B47F-16C	600	508	840	770	718	48	20-φ41	2990	425	1170	SMC-1	2030	2180
	700	610	910	840	788	50	24-φ41	3390	455	1250	SMC-2	3090	3330
	800	660	1020	950	989	52	24-φ41	3850	505	1370	SMC-2	3810	4110
	900	711	1120	1050	998	54	28-φ41	4260	545	1500	SMC-3	5160	5570
	1000	811	1255	1170	1110	56	28-φ48	4680	610	1670	SMC-3	6370	6880

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN2.5MPa									选配电装 E.A	WT(kg)	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2		110	120
	50	178	160	125	100	20	4-φ18	620	80	122	SMC-04	63	67
	65	190	180	145	120	22	8-φ18	710	90	152	SMC-04	82	90
	80	203	195	160	135	22	8-φ18	785	100	178	SMC-04	91	98
	100	229	230	190	160	24	8-φ23	910	110	220	SMC-04	105	113
Z9B43WF-25	125	254	280	220	188	28	8-φ25	1010	130	255	SMC-03	155	155
Z9B43F-25	150	267	300	250	218	30	8-φ25	1120	145	345	SMC-03	200	210
	200	292	360	310	278	34	12-φ23	1390	170	420	SMC-00	235	250
Z9B43WY-25	250	330	425	370	332	36	12-φ30	1550	210	495	SMC-00	390	420
Z9B43Y-25	300	356	485	430	390	40	16-φ30	1740	240	600	SMC-00	480	510
	350	381	550	490	448	44	16-φ34	1915	265	640	SMC-0	635	680
KZ9B43WF-25	400	406	610	550	505	48	16-φ34	2105	290	720	SMC-0	785	845
KZ9B43F-25	450	432	660	600	555	50	20-φ34	2370	325	798	SMC-0	1160	1250
Z9B47WF-25	500	457	730	660	610	52	20-φ41	2590	360	875	SMC-1	1460	1570
Z9B47F-25	600	508	840	770	718	56	20-φ41	2990	425	1170	SMC-2	2140	2300
	700	610	955	875	815	60	24-φ48	3390	455	1250	SMC-2	3610	3480
	800	660	1070	990	930	64	24-φ48	3850	505	1370	SMC-3	4320	4640
	900	711	1180	1090	1025	66	28-φ54	4260	545	1500	SMC-3	5620	6050
	1000	811	1305	1210	1140	68	28-φ58	4680	610	1670	SMC-3	6900	7430

总机：021-59546368



主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0MPa									选配电装 E.A	WT(kg)	
		L	D	D_1	D_2	b	Z-φd	H	H_1	H_2		110	120
Z9B43WF-40 Z9B43F-40 Z9B43WY-40 Z9B43Y-40 KZ9B43WF-40 KZ9B43F-40 Z9B47WF-40 Z9B47F-40	50	216	160	125	100	88	4-φ18	570	80	122	SMC-04	70	79
	65	241	180	145	120	110	8-φ18	680	90	152	SMC-04	90	100
	80	283	195	160	135	121	8-φ18	740	100	178	SMC-04	105	112
	100	305	230	190	160	150	8-φ23	910	110	220	SMC-04	125	128
	125	381	270	220	188	176	8-φ25	1010	130	255	SMC-03	185	190
	150	403	300	250	218	204	8-φ25	1110	145	345	SMC-03	235	250
	200	419	375	320	282	260	12-φ30	1390	170	420	SMC-00	385	413
	250	457	445	385	345	313	12-φ34	1550	210	495	SMC-00	520	560
	300	502	510	450	408	364	16-φ34	1740	240	600	SMC-0	770	825
	350	762	570	510	465	422	16-φ34	1915	265	640	SMC-0	1000	1040
	400	838	655	585	535	474	16-φ41	2105	290	720	SMC-1	1450	1550
	450	914	680	610	560	524	20-φ41	2370	325	798	SMC-1	1700	1830
	500	991	755	670	612	576	20-φ48	2590	360	875	SMC-2	2160	2330
	600	1143	890	795	730	678	20-φ54	2990	425	1170	SMC-2	3540	3800
	700	1346	995	900	835	768	24-φ54	3390	455	1250	SMC-3	4170	4770
	800	1524	1135	1030	960	876	24-φ58	3850	505	1370	SMC-3	5580	6300
	900	1727	1172	1089	1032	976	32-φ45	4750	545	1500	SMC-4	6200	6500

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN6.4MPa											WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z9B43WF-64 Z9B43F-64 Z9B43WY-64 Z9B43Y-64 KZ9B43WF-64 KZ9B43F-64 Z9B47WF-64 Z9B47F-64	50	250	175	135	105	88	26	4-φ23	650	108	158	SMC-04	131	135
	65	280	200	160	130	110	28	8-φ23	700	125	190	SMC-04	155	161
	80	310	210	170	140	121	30	8-φ23	750	145	225	SMC-04	225	240
	100	350	250	200	168	150	32	8-φ25	910	165	245	SMC-04	270	290
	125	400	295	240	202	176	36	8-φ30	1060	190	275	SMC-03	455	486
	150	450	340	280	240	204	38	8-φ34	1140	220	330	SMC-00	750	800
	200	550	405	345	300	260	44	12-φ34	1380	280	410	SMC-00	960	1030
	250	650	470	400	352	313	48	12-φ41	1575	330	490	SMC-0	1270	1360
	300	750	530	460	412	364	54	16-φ41	1725	380	570	SMC-0	1490	1600
	350	850	595	525	475	422	60	16-φ41	1930	410	770	SMC-1	2105	2340
	400	950	670	585	525	474	66	16-φ48	2210	470	882	SMC-2	2890	3150
	450	1050	670	630	570	524	70	20-φ48	2500	560	1015	SMC-2	3310	3760
	500	1150	800	705	640	576	70	20-φ54	2630	595	1115	SMC-2	3870	4130
	600	1350	930	820	750	678	76	20-φ58	2950	640	1265	SMC-3	4130	4720

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN10.0MPa											WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z9B43WF-100 Z9B43F-100 Z9B43WY-100 Z9B43Y-100 KZ9B43WF-100 KZ9B43F-100 Z9B47WF-100 Z9B47F-100	50	292	195	145	112	88	28	4-φ25	650	108	158	SMC-04	110	120
	65	330	220	170	138	110	32	8-φ25	700	125	190	SMC-04	135	145
	80	356	230	180	148	121	34	8-φ25	750	145	225	SMC-04	150	176
	100	432	265	210	172	150	38	8-φ30	910	165	245	SMC-03	195	240
	125	508	310	250	210	176	42	8-φ34	1060	190	275	SMC-03	255	280
	150	559	350	290	250	204	46	12-φ34	1140	220	330	SMC-00	400	450
	200	660	430	360	312	260	54	12-φ41	1380	280	410	SMC-0	544	600
	250	787	500	430	382	313	60	12-φ41	1575	330	490	SMC-0	720	850
	300	838	585	500	445	364	70	16-φ48	1725	380	570	SMC-1	1270	1390
	350	889	655	560	498	422	76	16-φ54	1930	410	770	SMC-1	1880	2020
	400	991	715	620	558	474	80	16-φ54	2210	470	882	SMC-2	2480	2750
	450	1092	770	975	615	524	84	16-φ58	2500	560	1015	SMC-2	2830	3210
	500	1194	870	760	690	576	90	20-φ54	2630	595	1115	SMC-3	3380	3640
	600	1397	990	875	800	678	95	24-φ58	2950	640	1265	SMC-3	3880	4460

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN15.0MPa											WT(kg)	
		L	D	D_1	D_2	D_6	b	Z-φd	H	H_1	H_2	D_0	110	112
Z9B43WF-150 Z9B43F-150 Z9B43WY-150 Z9B43Y-150 KZ9B43WF-150 KZ9B43F-150 Z9B47WF-150 Z9B47F-150	50	368	215	165	132	88	36	8-φ25	650	108	158	SMC-04	131	135
	65	419	245	190	152	110	44	8-φ30	700	125	190	SMC-04	155	161
	80	381	260	205	168	121	46	8-φ30	750	145	225	SMC-03	225	240
	100	457	300	240	200	150	48	8-φ34	910	165	245	SMC-03	270	290
	125	525	355	285	238	176	60	8-φ41	1060	190	275	SMC-00	455	486
	150	610	390	318	270	204	66	12-φ41	1140	220	330	SMC-0	750	800
	200	737	480	400	345	260	78	12-φ48	1380	280	410	SMC-1	960	1030
	250	838	580	485	425	313	88	12-φ54	1575	330	490	SMC-2	1270	1360
	300	965	665	570	510	364	110	16-φ54	1725	380	570	SMC-2	1490	1600
	350	1029	640	559	424	414.5	86	20-φ42	1930	410	770	SMC-2	2105	2340
	400	1130	705	616	481	471.5	89	20-φ45	2210	470	882	SMC-3	2890	3150
	450	1219	785	686	544	535	102	16-φ51	2500	560	1015	SMC-3	3310	3760
	500	1321	855	249.5	595	586	108	20-φ55	2630	595	1115	SMC-4	3870	4130
	600	1549	1040	901.5	703.5	694	140	20-φ68	2950	640	1265	SMC-4	4130	4720

总机：021-59546368



主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN1.0MPa								WT (kg)
		L	D	D_1	D_2	b	Z-φd	H	D_0	
Z44WF-16C Z44WY-16C KZ44WF-16C Z544WF-16C Z544WY-16C KZ544WF-16C Z6s44WF-16C Z6s44WY-16C KZ6s44WF-16C Z9B44WF-16C Z9B44WY-16C KZ9B44WF-16C	25	127	115	85	65	14	4-φ14	280	200	9
	32	140	135	100	78	16	4-φ18	322	200	12
	40	165	145	110	85	16	4-φ18	380	250	16
	50	178	160	125	100	16	4-φ18	415	250	26
	65	190	180	145	120	18	4-φ18	470	300	38
	80	203	195	160	135	20	8-φ18	540	300	46
	100	229	215	180	155	20	8-φ18	605	350	62
	125	325	245	210	185	22	8-φ18	785	350	96
	150	350	280	240	210	24	8-φ23	925	350	132
	200	400	335	295	265	26	12-φ23	1125	350	220
	250	450	405	355	320	30	12-φ25	1350	450	355
	300	500	460	410	375	30	12-φ25	1485	500	490
	350	550	520	470	435	34	16-φ25	1705	550	810
	400	600	580	525	485	36	16-φ30	1870	600	930
	450	650	640	585	545	40	20-φ30	2185	800	1230
	500	700	705	650	608	44	20-φ34	2335	800	1727
	600	800	840	770	718	48	20-φ41	2680	1000	2514

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm


产品型号 Type	公称通径 DN	PN2.5MPa								WT (kg)
		L	D	D_1	D_2	b	Z-φd	H	D_0	
Z44WF-25 Z44WY-25 KZ44WF-25 Z544WF-25 Z544WY-25 KZ544WF-25 Z6s44WF-25 Z6s44WY-25 KZ6s44WF-25 Z9B44WF-25 Z9B44WY-25 KZ9B44WF-25	25	127	115	85	65	16	4-φ14	280	200	9
	32	140	135	100	78	18	4-φ18	322	200	12
	40	165	145	110	85	18	4-φ18	380	250	16
	50	178	160	125	100	20	4-φ18	415	250	26
	65	190	180	145	120	22	8-φ18	470	300	38
	80	203	195	160	135	22	8-φ18	540	300	46
	100	229	230	190	160	24	8-φ23	605	350	62
	125	325	270	220	188	28	8-φ25	785	350	96
	150	350	300	250	218	30	8-φ25	925	350	132
	200	400	360	310	278	34	12-φ25	1125	350	220
	250	450	425	370	332	36	12-φ30	1350	450	355
	300	500	485	430	390	40	16-φ30	1485	500	490
	350	550	550	490	448	44	16-φ34	1705	550	810
	400	600	610	550	505	48	16-φ34	1870	600	930
	450	650	660	600	555	50	20-φ34	2185	800	1230
	500	700	730	660	610	52	20-φ41	2335	800	1727
	600	800	840	770	718	56	20-φ41	2680	1000	2514

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN4.0MPa								WT (kg)
		L	D	D_1	D_2	b	Z-φd	H	D_0	
Z44WF-40 Z44WY-40 KZ44WF-40 Z544WF-40 Z544WY-40 KZ544WF-40 Z6s44WF-40 Z6s44WY-40 KZ6s44WF-40 Z9B44WF-40 Z9B44WY-40 KZ9B44WF-40	25	165	115	85	65	16	4-φ14	280	200	9
	32	178	135	100	78	18	4-φ18	322	200	13
	40	190	145	110	85	18	4-φ18	380	250	17
	50	216	160	125	100	20	4-φ18	415	250	27
	65	241	180	145	120	22	8-φ18	470	300	40
	80	285	195	160	135	22	8-φ18	540	300	48
	100	305	230	190	160	24	8-φ23	605	350	65
	125	381	270	220	188	28	8-φ25	785	350	101
	150	403	300	250	218	30	8-φ25	925	350	139
	200	419	375	320	282	38	12-φ30	1125	350	231
	250	157	445	385	345	42	12-φ34	1350	450	373
	300	502	510	450	408	46	16-φ34	1485	500	515
	350	762	570	510	465	52	16-φ34	1705	550	851
	400	838	655	585	535	58	16-φ41	1870	600	977
	450	914	680	610	560	60	20-φ41	2185	800	1292
	500	991	755	670	612	62	20-φ48	2335	800	1813
	600	1143	890	795	730	62	20-φ54	2680	1000	2640

总机：021-59546368




主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN6.4MPa								WT (kg)
		L	D	D_1	D_2	b	Z-φd	H	D_0	
Z44WF-64 Z44WY-64 KZ44WF-64 Z544WF-64 Z544WY-64 KZ544WF-64 Z6s44WF-64 Z6s44WY-64 KZ6s44WF-64 Z9B44WF-64 Z9B44WY-64 KZ9B44WF-64	25	216	135	100	78	58	4-φ18	314	200	10
	32	229	150	110	82	66	4-φ23	361	200	13
	40	241	165	125	95	76	4-φ23	426	250	18
	50	250	175	135	105	88	4-φ23	465	250	29
	65	280	200	160	130	110	8-φ23	526	300	42
	80	310	210	170	140	121	8-φ23	605	300	51
	100	350	250	200	168	150	8-φ25	678	350	69
	125	400	295	240	202	176	8-φ30	879	350	107
	150	450	340	280	240	204	8-φ34	1036	450	147
	200	550	405	345	300	260	12-φ34	1260	450	244
	250	650	470	400	352	313	12-φ41	1512	500	394
	300	750	530	460	412	364	16-φ41	1663	500	544
	350	850	595	525	475	422	16-φ41	1910	600	899
	400	950	670	585	525	474	16-φ48	2094	800	1032
	450	1050	670	630	570	524	20-φ48	2447	800	1365
	500	1150	800	705	640	576	20-φ54	2615	1000	1917
	600	1350	930	820	750	678	20-φ58	3002	1000	2791





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN16.0/20.0/25.0MPa					WT (kg)
		L	D	H_2	H	D_0	
Z63Y-160	40	260	55	100	380	350	80
	50	300	68	112	400	350	90
	65	320	83	138	440	350	110
	80	360	102	163	500	350	160
	100	450	121	193	540	470	210
	150	500	168	272	620	470	270
Z63Y-200	50	300	68	122	400	350	100
	65	320	89	148	440	350	120
	80	360	108	170	500	350	180
	100	450	128	200	540	470	220
	150	500	186	283	620	470	280
Z63Y-250	50	310	68	123	400	350	100
	65	340	89	148	440	350	120
	80	380	108	172	500	350	180
	100	480	125	205	540	470	220
	150	580	186	288	620	470	290


主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN32.0/40.0MPa					WT (kg)
		L	D	H_2	H	D_0	
Z63Y-320	50	310	70	125	400	350	125
	65	340	89	150	440	350	150
	80	380	108	174	500	470	174
	100	480	140	208	540	470	208
	150	580	194	300	620	600	300
Z63Y-400	50	240	75	127	230	350	127
	65	290	101	152	250	350	152
	80	350	110	183	340	470	183
	100	380	146	217	375	470	217

总机：021-59546368





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN16.0/20.0/25.0MPa									WT (kg)
		L	D	D_1	D_2	b	Z–φd	H	H_2	D_0	
Z43Y–160	50	260	216	165.1	95.25	46	8–φ26	520	112	350	110
	65	315	244	190.5	107.95	49.2	8–φ29	570	138	350	140
	80	380	267	203.2	136.53	55.6	8–φ32	625	163	350	180
	100	425	292	235	149.23	52.4	8–φ32	650	193	470	230
	150	530	342	280	181	62	12–φ35	700	272	470	290
	200	620	392	362	231	92.10	12–φ35	760	352	600	380
Z43Y–200	50	340	216	165.1	95.25	46	8–φ26	530	122	350	110
	65	380	244	190.1	107.95	49.2	8–φ29	580	148	350	140
	80	380	267	203.2	136.53	55.6	8–φ32	640	170	350	180
	100	450	292	235	149.23	52.4	8–φ32	670	200	470	230
	150	540	342	280	181	62	12–φ35	730	283	470	290
Z43Y–250	50	350	216	165.1	95.55	46	8–φ26	550	123	350	110
	65	400	244	190.5	107.95	49.2	8–φ29	590	148	350	140
	80	420	267	203.2	136.53	55.60	8–φ32	650	172	350	200
	100	470	311	241.3	161.93	61.90	8–φ35	680	250	470	240
	150	540	361	329	208.93	62	12–φ35	740	288	470	300

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN32.0/40.0MPa									WT (kg)
		L	D	D_1	D_2	b	Z–φd	H	H_2	D_0	
Z43Y–320	50	360	216	165.1	95.25	46	8–φ26	570	125	350	120
	65	410	244	190.1	107.95	49.2	8–φ29	600	150	350	160
	80	445	267	203.2	136.53	55.6	8–φ32	660	174	470	220
	100	490	311	241.3	161.93	61.9	8–φ35	710	208	470	250
	150	620	361	329	208.93	92.1	12–φ35	760	300	600	320
Z43Y–400	50	375	216	165.1	95.25	48	8–φ26	577	127	350	140
	65	420	244	190.5	107.95	52.2	8–φ29	617	152	350	180
	80	460	267	203.2	136.53	59	8–φ35	683	183	470	235
	100	510	311	241.3	161.93	66	8–φ35	725	217	470	270

主要特点

全通径，明杆带支架
中法兰螺栓连接
带导向的弹性闸板
阀杆升降，手轮不升降
伞齿轮操作选配
标准法兰连接
对焊连接



CHIEF FEATURES


FULL PORT,OUTSIDE SCREW AND YOKE(OS&Y)
BOLTE D BONNET
FLEXIBLE WEDGE, FULLY GUIDED
RISING STEM AND NON-RISING HANDWHEEL
AVAILABLE WITH GEAR OPERATOR
FLANGED ENDS
BUTT-WELDING ENDS

产品规范Product Specification

产品规范 Product Specification	设计规范 Design Spec.	结构长度 Face to Face	连接法兰 Flange End	试验与检验 Test &inspection	压力-温度 Pressure-Temp.	产品标识 Marking	供货规范 Supply
	API 600	ANSI B16.10	ANSI B16.5	API 598	ANSI B16.34	MSS SP-25	API 608
	API 6D	API 6D		API 6D			API 6D

主要零部件材料Main Part Material

零件名称	零部件材料Part material				Part Name
阀体/阀盖	A216-WCB	A217-WC6	A352-LCB	A351-CF8M	Body/Bonnet
阀　　板	A182-WCB	A217-WC6	A352-LCB	A351-CF8M	Wedge
阀　　杆	A182-F6a	A182-F11	A182-F6a	A182-F316	Stem
填　　料	柔性石墨/Flexible Graphite			聚四氟乙烯/PTFE	Packing
垫　　片	18-/柔性石墨/18-8Flexible Graphite				Gasket
螺　　栓	A193-B7	A193-B7	A193-B7M	A193-B8	Bolt
适用温度	-29～425℃	-29～550℃	-46～350℃	-40～200℃	Applicable Temp.
适用介质	水、油品、蒸汽 Water、Oil、Steam	蒸汽、油品 Steam、Oil	丙烷、乙烯 Propane Ethylene	硝酸类 Nitric Acid	Applicable Medium



主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	NPS	DN	Class 150Lb								WT (kg)
	in	mm	L	D	D_1	D_2	b	Z–φd	H	D_0	
Z40H–150Lb (Body:WCB) Z40H–150LbP (Body:CF8) Z40H–150Lb (Body:CF8) Z40H–150LbR (Body:CF8M) Z40H–150LbPL (Body:CF3) Z41H–1500LbRL (Body:CF3M)	2	50	178	152	120.5	92	16	4–φ19	323	200	18
	2 1/2″	65	190	178	139.5	105	18	4–φ19	347	250	28
	3	80	203	190	152.5	127	19	4–φ19	383	250	30
	4	100	229	229	190.5	157	24	8–φ19	457	300	50
	5	125	254	254	216	186	24	8–φ22	632	300	63
	6	150	267	279	241.5	216	26	8–φ22	635	350	85
	8	200	292	343	298.5	270	29	8–φ22	762	350	128
	10	250	330	406	362	324	31	12–φ25	895	400	220
	12	300	356	483	432	381	32	12–φ25	1080	500	310
	14	350	381	533	476	413	35	12–φ29	1295	600	450
	16	400	406	597	540	470	37	16–φ29	1435	600	550
	18	450	432	635	578	533	40	16–φ32	1626	650	700
	20	500	457	698	635	584	43	20–φ32	1829	650	910
	24	600	508	813	749.5	692	48	20–φ35	2175	700	1130
	28	700	610	984	914.5	857	75	28–φ35	2695	700	2230

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	NPS	DN	Class 300Lb								WT (kg)
	in	mm	L	D	D_1	D_2	b	Z–ϕd	H	D_0	
Z40H–300Lb (Body:WCB) Z40H–300LbP (Body:CF8) Z40H–300Lb (Body:CF8) Z40H–300LbR (Body:CF8M) Z40H–300LbPL (Body:CF3) Z41H–300LbRL (Body:CF3M)	2	50	216	165	124	92	22	8–ϕ19	330	250	30
	2 1/2″	65	241	190	149	105	25	8–ϕ22	368	250	36
	3	80	283	210	168.5	127	29	8–ϕ22	394	300	61
	4	100	305	254	200	157	32	8–ϕ22	473	300	77
	5	125	381	279	235	186	35	8–ϕ22	660	350	106
	6	150	403	318	270	216	37	12–ϕ22	711	350	153
	8	200	419	381	330	270	40	12–ϕ25	813	400	286
	10	250	457	444	387.5	324	48	16–ϕ29	1003	500	412
	12	300	502	521	451	381	51	16–ϕ32	1137	600	576
	14	350	762	584	514.5	413	54	20–ϕ32	1489	600	886
	16	400	838	648	571.5	470	57	20–ϕ35	1581	650	1175
	18	450	914	711	628.5	533	60	24–ϕ35	2017	838	1301
	20	500	991	775	686	584	64	24–ϕ35	2228	889	1672
	24	600	1143	914	813	692	70	24–ϕ41	2650	1092	2562

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	NPS	DN	Class 600Lb								WT (kg)
	in	mm	L	D	D_1	D_2	b	Z–ϕd	H	D_0	
Z40H–600Lb (Body:WCB) Z40H–600LbP (Body:CF8) Z40H–600Lb (Body:CF8) Z40H–600LbR (Body:CF8M) Z40H–600LbPL (Body:CF3) Z41H–600LbRL (Body:CF3M)	2	50	292	165	127	92	33	8–ϕ19	510	254	44
	2 1/2″	65	330	190	149	100	36	8–ϕ22	554	254	60
	3	80	356	210	168	127	39	8–ϕ22	595	305	80
	4	100	432	273	216	157	45	8–ϕ25	712	356	145
	5	125	508	330	266.5	186	52	8–ϕ29	826	406	236
	6	150	559	356	292	216	55	12–ϕ29	995	508	309
	8	200	660	419	349	270	63	12–ϕ32	1157	610	522
	10	250	787	508	432	324	71	16–ϕ35	1373	686	779
	12	300	838	559	489	381	74	20–ϕ35	1603	686	1108
	14	350	889	603	527	413	77	20–ϕ38	1930	762	1503
	16	400	991	686	603	470	84	20–ϕ41	2032	889	1939
	18	450	1092	743	654	533	90	20–ϕ44	2286	889	2733
	20	500	1194	813	724	584	96	24–ϕ44	2591	1118	3214
	24	600	1397	940	838	692	109	24–ϕ52	3124	1118	4177

磅级低温闸阀 ANSI Cryogenic Gate Valve

上嘉阀门

主要特点

全通径，明杆带支架

中法兰螺栓连接

带导向的弹性闸板

美标结构改进型

加长保温颈

伞齿轮操作选配

标准法兰连接



CHIEF FEATURES

FULL PORT,OUTSIDE SCREW AND YOKE(OS&Y)

BOLTE D BONNET

FLEXIBLE WEDGE, FULLY GUIDED

STRUCTUIRE IMPROVE ON API

EXTENSION GOLDING NECK

AVAILABLE WITH GEAR OPERATOR

FLANGED ENDS


产品规范Product Specification

产品规范 Product Specification	设计规范 Design Spec.	结构长度 Face to Face	连接法兰 Flange End	试验与检验 Test &inspection	压力-温度 Pressure-Temp.	产品标识 Marking	供货规范 Supply
	API 600	ANSI B16.10	ANSI B16.5	API 598	ANSI B16.34	MSS SP-25	API 600

主要零部件材料Main Part Material

零件名称	零部件材料Part material							Part Name
阀　体	A352-LCB	A352-LC1	A352-LC2	A352-LC3	A352-LC4	A351-CF8	A351-CF3	Body
阀　盖	A352-LCB	A352-LC1	A352-LC2	A352-LC3	A352-LC4	A351-CF8	A351-CF3	Bonnet
阀　板	A352-LCB	A352-LC1	A352-LC2	A352-LC3	A352-LC4	A351-CF8	A351-CF3	Wedge
阀　杆	A182-F431			A182-F304			A182-F304L	Stem
密封副	STL+STL			STL+STL			STL+STL	Hard Trim
填　料	柔性石墨 Flexible Graphite(聚四氟乙烯/PTFE)							Packing
垫　片	18-8柔性石墨Flexible Graphite							Gasket
螺　栓	A193-B7M			A193-B8		A193-B8M		Bolt
适用温度	-46℃	-60℃	-73℃	-101℃	-115℃	-196℃	-196℃	Applicable Temp.
适用介质	丙烷、丙烯 、甲醇、乙烷、煤气、液氨 Propane,propylene,Methanol,Ethanol,Coal-Gas,Liquid Ammonia							Applicable Medium





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	NPS	DN	Class 150Lb								WT (kg)
	in	mm	L	D	D_1	D_2	b	Z-φd	H	D_0	
DZ40Y-150Lb	1″	25	127	108	79.5	51	12	4-φ15	350	100	9
	1¼″	32	140	117	89	64	13	4-φ15	385	100	11
	1½″	40	165	127	98.5	73	15	4-φ15	420	140	15
	2″	50	178	152	120.5	92	16	4-φ19	540	200	23
	2½″	65	190	178	139.7	105	18	4-φ19	610	250	27
	3″	80	203	190	152.5	127	19	4-φ19	690	250	40
	4″	100	229	229	190.5	157	23.9	8-φ19	780	250	50
	5″	125	254	254	215.9	186	25.4	8-φ22	930	300	70
	6″	150	267	279	241.5	216	28.5	8-φ22	980	300	85
	8″	200	292	343	298.5	270	30.2	8-φ22	1180	350	135
	10″	250	330	406	362	324	31.2	12-φ25	1390	400	180
	12″	300	356	483	432	381	31.8	12-φ25	1620	450	265
	14″	350	381	533	476.5	413	35	12-φ29	1810	500	420
	16″	400	406	597	539.5	470	36.6	16-φ29	1970	600	550

总机：021-59546368

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	NPS	DN	Class 300Lb								WT (kg)
	in	mm	L	D	D_1	D_2	b	Z-φd	H	D_0	
DZ40Y-300Lb	1″	25	165	124	89	51	18	4-φ19	360	125	10
	1¼″	32	178	133	98.5	63	19	4-φ19	390	160	15
	1½″	40	190	156	114.5	73	21	4-φ22	420	160	20
	2″	50	216	165	127	92	22.3	8-φ19	575	200	30
	2½″	65	241	190	149.4	105	25	8-φ22	635	250	38
	3″	80	283	210	168	127	28.5	8-φ22	715	250	51
	4″	100	305	256	200	157	31.8	8-φ22	785	250	79
	5″	125	381	279	235	186	35	8-φ22	865	300	115
	6″	150	403	318	270	216	36.6	12-φ22	1025	350	140
	8″	200	419	381	330	270	41.3	12-φ25	1225	400	220
	10″	250	457	444	387.5	324	47.7	16-φ29	1440	450	290
	12″	300	502	521	451	381	50.8	16-φ32	1665	500	410
	14″	350	762	584	514.5	413	54	20-φ32	1880	600	600
	16″	400	838	648	571.5	470	57.2	20-φ35	2050	600	750

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	NPS	DN	Class 600Lb								WT (kg)
	in	mm	L	D	D_1	D_2	b	Z-φd	H	D_0	
DZ40Y-600Lb	1″	25	216	124	89	51	18	4-φ19	380	160	15
	1¼″	32	229	133	98.5	63	19	4-φ19	430	200	20
	1½″	40	241	156	114.5	73	23	4-φ22	575	200	30
	2″	50	292	165	127	92	25.4	8-φ19	630	250	45
	2½″	65	330	190	149.4	100	29	8-φ22	700	250	58
	3″	80	356	210	168	127	31.8	8-φ22	760	250	75
	4″	100	432	273	216	157	38.1	8-φ25	900	350	126
	5″	125	511	330	266.5	186	44	8-φ29	990	350	186
	6″	150	559	356	292	216	47.7	12-φ29	1070	450	260
	8″	200	660	410	349	270	55.6	12-φ32	1280	500	385
	10″	250	787	508	432	324	63.5	16-φ35	1500	600	500
	12″	300	838	559	489	381	66.7	20-φ35	1740	680	574
	14″	350	889	603	527	413	70	20-φ39	1890	720	740
	16″	400	991	686	603	470	77	20-φ41	2125	720	920

主要特点

缩径，明杆带支架
中法兰螺栓连接
刚性闸板
美标结构改进型
阀杆升降,手轮不升降
法兰连接
内螺纹连接
承插焊连接
对焊连接





CHIEF FEATURES

REDUCED,OUTSIDE SCREW AND YOKE(OS&Y)
BOLTE D BONNET
RIGIDITY WEDGE FULLY GUIDED
STRUCTUIRE IMPROVE ON API
RISING STEM AND NON--RISING HANDWHEEL
FLANGED ENDS
INSIDE SCREW ENDS
SCOKET WELD ENDS
BULL--WELDING ENDS

产品规范Product Specification


产品规范 Product Specification	设计规范 Design Spec.	结构长度 Face to Face	对焊法兰 BW End	试验与检验 Test &Check	压力-温度 Pressure-Temp.	产品标识 Marking	供货规范 Supply
	JB/T 7746	JB/T 7746	JB/T 79	JB/T 9092	GB/T 9131	GB/T 12220	JB/T 7928


主要零部件材料Main Part Material

零件名称	零部件材料Part material		Part Name
阀体/阀盖	25	1Cr18Ni9Ti	Body/Bonnet
阀板/阀瓣	2Cr13	1Cr18Ni9Ti	Wedge/Disc
阀　　杆	2Cr13	1Cr18Ni9Ti	Stem
密 封 圈	1Cr13+HF	1Cr18Ni9Ti+STL	Seal Ring
填　　料	柔性石墨/Flexible Graphite	聚四氟乙烯/PTFE	Packing
垫　　片	18-18/柔性石墨/18-8/Flexible Graphite		Gasket
螺　　栓	35/35CrMo	1Cr18Ni9Ti	Bolt
适用温度	-29～425℃	-40～200℃	Applicable Temp.
适用介质	水、油品、蒸汽 Water、Oil、Steam	销酸类 Nitric Acid	Applicable Medium

总机：021-59546368







主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN1.6/2.5/4.0/6.4MPa								WT (kg)
		L	d	S	L_1	T	L_2	H	D_0	
Z41H–16C Z41H–25 Z41H–40 Z11H–16C Z11H–25 Z11H–40 Z61H–16C Z61H–25 Z61H–40	15	90	13	22.5	10	½″	15	151	118	6.9
	20	100	18	28.5	11	¾″	17	182	130	9.8
	25	120	23	24.5	12	1	19	197	150	13.5
	32	130	28	43	14	1¼″	21	212	180	19.5
	40	150	36	49	15	1½″	21	231	180	28.5
	50	155	45	61	16	2″	25	253	180	30.3
Z41H–64 Z11H–64 Z61H–64	15	90	13	22.5	10	½″	15	151	118	7.7
	20	100	18	28.5	11	¾″	17	182	130	11.3
	25	120	23	34.5	12	1″	19	197	150	16.8
	32	130	28	43	14	1¼″	21	212	180	21.2
	40	150	36	49	15	1½″	21	231	180	32.6
	50	155	45	61	16	2″	25	253	180	35

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	PN10.0/16.0MPa Class800Lb								WT (kg)
		L	d	S	L_1	T	L_2	H	D_0	
Z41Y–100 Z11Y–100 Z61Y–100	15	90	13	22.5	10	½″	15	151	118	7.8
	20	100	18	28.5	11	¾″	17	182	130	12.5
	25	120	23	24.5	12	1	19	197	150	17.5
	32	130	28	43	14	1¼″	21	212	180	23.5
	40	150	36	49	15	1½″	21	231	180	38.5
	50	155	45	61	16	2″	25	253	180	42.2
Z41Y–160 Z11Y–160 Z61Y–160 Z41Y–800Lb Z11Y–800Lb Z61Y–800Lb	15	90	13	22.5	10	½″	15	151	118	8.0
	20	100	18	28.5	11	¾″	17	182	130	13.6
	25	120	23	34.5	12	1″	19	197	150	19.2
	32	130	28	43	14	1¼″	21	212	180	25.1
	40	150	36	49	15	1½″	21	231	180	41.6
	50	155	45	61	16	2″	25	253	180	49.0

弹性座封闸阀 Flexible Seal Gate Valve

主要特点

全通径，暗杆操作
中法兰螺栓连接
整体包胶闸板
平底式阀座，无杂质沉淀
多重动密封设计
阀体外表粉体环氧树指涂装
法兰连接
生饮卫生场合适用





CHIEF FEATURES

FULL PORT,NONRISING STEM OPERATE
BOLTED BONNET
WEDGE INTEGRAL
MULTI--MOVE SEAL DESIGN
SURFACE PAINTING RESIN
FLANGED ENDS
SUITABLE FOU DUINK CONDITION


产品规范Product Specification


产品规范 Product Specification	设计规范 Design Spec.	结构长度 Face to Face	连接法兰 Flange End	试验与检验 Test &inspection	产品标识 Marking	供货规范 Supply
	AWWA C509-94	GB/T 12221	GB 9113	GB/T 13927	GB/T 12220	JB/T 7928

主要零部件材料Main Part Material

零件名称	零部件材料Part material		Part Name
阀体/阀盖	HT200	QT450-10	Body/Bonnet
阀板/阀瓣	HT200+NBR	QT200+NBR	Wdege/Disc
阀　　杆	2Cr13	2Cr13	Stem
填　　料	NBR	NBR	Packing
适用温度	-15～121℃	-30～121℃	Applicable Temp.
适用介质	水、海水、污水、油品、纸浆等 Water,Sea Water,Sewage,Oil,Paper PulP Etc.		Applicable Medium

总机：021-59546368





主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	L	D	D_1		D_2	b	Z-Φd		H	D_0
				PN10	PN16			PN10	PN16		
Z45X/RVCX-10 Z45X/RVCX-16 Z45X/RVCX-10 Z45X/RVCX-16	50	180	100	125	–	155	18	4-Φ19	4-Φ19	365	200
	65	190	118	145	–	185	19	4-Φ19	4-Φ19	442	200
	80	240	125	160	–	211	21	8-Φ19	8-Φ19	540	250
	100	250	152	180	–	238	21	8-Φ19	8-Φ19	616	250
	125	254	184	210	–	250	19	8-Φ19	8-Φ19	710	340
	150	280	204	240	–	290	22	8-Φ23	8-Φ23	812	340
	200	300	256	295	–	342	23	8-Φ23	12-Φ23	1010	400
	250	380	308	350	355	410	24	12-Φ23	12-Φ28	1180	450
	300	400	362	400	410	464	25	12-Φ23	12-Φ28	1385	500
	350	430	414	460	470	530	26	16-Φ23	16-Φ28	1542	560
	400	406	480	215	525	580	28	16-Φ28	16-Φ31	1759	640
	450	432	530	565	585	640	30	20-Φ28	20-Φ31	1972	720
	500	457	585	620	650	715	31.5	20-Φ28	20-Φ34	–	720
	600	508	685	685	770	840	36	20-Φ31	20-Φ37	–	800

主要外形和连接尺寸 Main External and Connection Dimension

单位Unit:mm

产品型号 Type	公称通径 DN	L	PN1.0MPa				PN1.0MPa				D_2	H	D_0
			D	D_1	b	Z-Φd	D	D_1	b	Z-Φd			
Z41X/RRHX-10 Z41X/RRHX-16 Z941X/RRHX-10 Z941X/RRHX-16	40	165	160	110	18	4-Φ18	150	110	18	4-Φ18	84	75	160
	50	178	165	125	20	4-Φ18	165	125	20	4-Φ18	99	82	160
	65	190	180	145	20	4-Φ18	285	145	20	4-Φ18	118	92	180
	80	203	200	160	22	4-Φ18	200	160	20	4-Φ18	132	100	180
	100	229	220	180	22	8-Φ18	220	180	22	8-Φ18	156	110	240
	125	254	250	210	24	8-Φ18	250	210	22	8-Φ18	184	133	280
	150	267	285	240	24	8-Φ22	285	240	24	8-Φ22	211	142	340
	200	292	340	295	26	8-Φ22	340	295	24	12-Φ22	166	170	400
	250	330	395	350	28	12-Φ22	405	355	26	12-Φ26	319	202	450
	300	356	440	400	28	12-Φ22	460	410	28	12-Φ26	370	230	500
	350	381	520	460	30	16-Φ22	520	470	30	16-Φ26	429	260	560
	400	406	580	515	32	16-Φ26	580	525	32	16-Φ30	480	290	640
	450	432	640	565	32	20-Φ26	640	585	34	20-Φ30	530	320	720
	500	457	715	620	34	20-Φ26	715	650	36	20-Φ33	585	357	720
	600	508	810	725	36	20-Φ30	840	725	38	20-Φ36	685	420	800